

## Product Specification

### CO5W-30D2

#### Fully Synthetic Dexos2 Engine Oil

| 1 L        | 4 L        | 5 L        | 20 L        | 60 L        | 200L         |
|------------|------------|------------|-------------|-------------|--------------|
| CO5W30D2-1 | CO5W30D2-4 | CO5W30D2-5 | CO5W30D2-20 | CO5W30D2-60 | CO5W30D2-200 |

#### LEVELS OF QUALITY

The lubricant CO5W-30D2 complies with the following international specifications:

ACEA C3; API SN, SM, CF; BMW LONG LIFE 04; FIAT 9.55535.S2, S3; GM DEXOS 02; MB 229.52, 229.51, 229.31, 226.5; PORSCHE C30; PSA B71 2297; VW 502.00, 505.00, 505.01

#### DESCRIPTION

**CO5W-30D2** is a Long Life 100% synthetic lubricant with mid ash content (Mid SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

**CO5W-30D2** has been specifically designed to satisfy the latest ACEA C3 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

| SAE Scale              |            | 5W/30 |
|------------------------|------------|-------|
| Density at 15°C.Kg/dm3 | ASTM D1298 | 0.850 |
| Viscosity at 100°C.cSt | ASTM D445  | 11.8  |
| Viscosity Index        | ASTM D2270 | 150   |
| Flammability V.A.°C    | ASTM D92   | 216   |
| Pour Point °C          | ASTM D97   | -36   |
| S.A.                   | ASTM D874  | 0.79  |
| T.B.N.                 | ASTM D2896 | 6.8   |

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 5W-30D2\_REV.5 October 2021**