
Product Specification

CO5W-30LL

Fully Synthetic Long Life Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W30LL-1	CO5W30LL-4	CO5W30LL-5	CO5W30LL-20	CO5W30LL-60	CO5W30LL-200

LEVELS OF QUALITY

The lubricant CO5W-30LL complies with the following international specifications:

ACEA C2, C3; API SN, SM, CF; BMW LONG LIFE 04; FIAT 9.55535.S3; FORD WSS-M2C917-A; MB 226.51, 229.31, 229.51, 229.52; PORSCHE C30; VW 504.00-507.00, 505.01, 506.01

DESCRIPTION

CO5W-30LL is a Long Life 100% synthetic Mid SAPS lubricant produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

CO5W-30LL has been specifically designed to satisfy the latest AUDI-Volkswagen, BMW e Mercedes-Benz specifications for motorizations with prolonged service intervals and fitted with particulate filtration systems, are maintenance-free and without fuel additives.

SAE Scale		5W/30
Density at 15°C.Kg/dm3	ASTM D1298	0.845
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	165
Flammability V.A.°C	ASTM D92	214
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.2

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 5W-30LL_REV.5 October 2021