

Product Specification

CO5W-30Z

Fully Synthetic ZETEC Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W30Z-1	CO5W30Z-4	CO5W30Z-5	CO5W30Z-20	CO5W30Z-60	CO5W30Z-200

LEVELS OF QUALITY

The lubricant CO5W-30Z complies with the following international specifications:

ACEA A5/B5, A1/B1; API SL, CF; FORD WSS M2C-913C, 913D; FIAT 9.55535-G1, N1

DESCRIPTION

CO5W-30Z is a synthetic multigrade lubricant with the specific Fuel Economy (FE) formula which has been produced to reach the highest performance and reliability standards in modern concept petrol and diesel engines. It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures). It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.). It is recommended to always observe the oil change interval as suggested by the car manufacturer.

SAE Scale		5W/30
Density at 15°C.Kg/dm ³	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11
Viscosity Index	ASTM D2270	145
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-30
T.B.N.	ASTM D2896	8

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 5W-30Z_REV.3 October 2021