

## Product Specification

### CO5W-40PD

#### Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W40PD-1	CO5W40PD-4	CO5W40PD-5	CO5W40PD-20	CO5W40PD-60	CO5W40PD-200

#### LEVELS OF QUALITY

The lubricant CO5W-40PD complies with the following international specifications:

ACEA C3; API SN, SM, CF; BMW LONG LIFE 04; FIAT 9.55535.S2, GH2; FORD WSS-M2C 917A; GM DEXOS 02; MB 226.5, 229.31, 229.51; PORSCHE A40; PSA B71 2297; RENAULT RN0700, RN0710; VW 502.00, 505.00, 505.01.

#### DESCRIPTION

**CO5W-40PD** is a 100% synthetic MID SAPS lubricant with low ash content produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Furthermore CO5W-40PD has been specifically designed to satisfy the latest ACEA C3 specifications with a mid-ash content and is recommended for engines equipped with particulate filtration systems, maintenance-free and without fuel additives.

SAE Scale		5W/40
Density at 15°C.Kg/dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	13.2
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-33
S.A.	ASTM D874	0.75
T.B.N.	ASTM D2896	7.4

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 5W-40PD\_REV.5 October 2021**