

Product Specification

CODOT4

Fully Synthetic Brake Fluid

1 L	4 L	5 L	20 L	60 L	200L
CODOT4-1	CODOT4-4	CODOT4-5	CODOT4-20	CODOT4-60	CODOT4-200

LEVELS OF QUALITY

The lubricant CODOT4 complies with the following international specifications:

SAE J1703, FMVSS 116 DOT3, DOT4; ISO 4925; CUNA NC-956 DOT4; IVECO 18-1820

DESCRIPTION

DOT4 has been specifically designed for hydraulic circuits which apply disc brakes or brake-shoes fitted on cars, heavy vehicles, motorbikes, agricultural machines, earthmoving equipment, and industrial machinery in general.

It is suitable for the use in all braking systems, whenever it is required a fluid at DOT4 level, except for ESP/ASR braking systems.

It may be used as a top-up in systems designed for a fluid at DOT3 level, but it must not be used whenever it is required a fluid at DOT5 level. It ensures the maximum protection against the vapour lock phenomenon, that it is to say the formation of vapour bubbles which impairs the quality of brakes.

Specific weight at 20°C	ASTM D1298	1030
Colour	VISUAL	Straw Yellow
Flammability V.A.°C	ASTM D92	100
Boiling point T.Q.		280
Boiling point after humidification		140
Viscosity at 40°C	ASTM D445	lower than 150 0
Viscosity at 100°C	ASTM D445	higher than 2
pH		9 up 11.5

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline DOT4_REV.3 February 2022