

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** J03140 - JLM Petrol Air Intake Cleaner 500ml PRO
- **Article number:** L23140
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU21 Consumer uses: Private households / general public / consumers
- **Product category** PC35 Washing and cleaning products (including solvent based products)
- **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
- **Application of the substance / the preparation** Cleaner solvent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
INO "Nwdtlecpw"DKX0
Schiphol Boulevard"/"1118"BG"Schiphol
The Netherlands
Tel: +31(0)20 201 4995
Fax: /
E-mail: kphqB lno nwdtlecpw.com
- **Further information obtainable from:** Research & Development/E-mail: info@jlm lubricants.com
- **1.4 Emergency telephone number:** During normal opening hours: Tel: +31(0)20 201 4995

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

R36/38: Irritating to eyes and skin.

(Contd. on page 2)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 1)



F+; Extremely flammable

R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08

Signal word Danger**Hazard-determining components of labelling:**

xylene (mix)

Naphtha (petroleum), hydrotreated light

2-butoxyethanol

butanone / MEK

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.

(Contd. on page 3)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· 3.1 Substances

· Additional information:

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene (mix) Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-<50%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone / MEK Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	20-<25%
CAS: 64742-49-0 EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Naphtha (petroleum), hydrotreated light Xn R65; Xi R38; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-<20%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Xi R36; F R11 R67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	10-<25%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Xn R20/21/22; Xi R36/38 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1.0-<2.5%

· 3.2 Mixtures

· **Description:** Active substance with propellant

· **Dangerous components:** -

· Ingredients according to detergents guideline 648/2004/EC

aliphatic hydrocarbons	≥ 30%
aromatic hydrocarbons	15 - 30%

· Additional information:

4 First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

(Contd. on page 4)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 3)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurized containers.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 4)

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

78-93-3 butanone / MEK

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

74-98-6 propane

OEL	Short-term value: 3600 mg/m ³ , 2000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm
-----	---

111-76-2 2-butoxyethanol

WEL	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV
-----	---

· **DNELs**

78-93-3 butanone / MEK

Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer)
		600 mg/m ³ (Worker)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer)
		2035 mg/m ³ (Worker)

67-63-0 propan-2-ol

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)
		888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m ³ (Consumer)
		500 mg/m ³ (Worker)

(Contd. on page 6)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 5)

· Ingredients with biological limit values:

1330-20-7 xylene (mix)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

78-93-3 butanone / MEK

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

111-76-2 2-butoxyethanol

BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid
------	---

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 6)

· **Body protection:** Use protective suit.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Aerosol

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

-44 °C

· **Flash point:**

-97 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

200 °C

· **Decomposition temperature:**

Not determined.

· **Self-igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**
Lower:

0.7 Vol %

Upper:

12.0 Vol %

· **Vapour pressure at 20 °C:**

5 Bar

· **Density at 20 °C:**

0.745 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**
Dynamic:

Not determined.

Kinematic:

Not determined.

· **Solvent content:**
Organic solvents:

99.9 %

Solids content:

0.1 %

· **9.2 Other information**

No further relevant information available.

10 Stability and reactivity

· **10.1 Reactivity**

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene (mix)

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

78-93-3 butanone / MEK

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		5000 mg/kg (rbt)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2800 mg/kg (rabbit)
Inhalative	LC50/4 h	>23 mg/l (rat)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m3 (rat)

111-76-2 2-butoxyethanol

Oral	LD50	300 mg/kg (rabbit)
		470 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

1330-20-7 xylene (mix)

EC50/48h	3.2-9.5 mg/l (Daphnia magna)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)

78-93-3 butanone / MEK

EC50/48h	308 mg/l (Daphnia magna)
LC50/96h	2993 mg/l (Pimephales promelas)

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50/48h	3 mg/l (Daphnia magna)
----------	------------------------

(Contd. on page 9)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 8)


EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
LOEC (21 days)	0.32 mg/l (Daphnia magna)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
67-63-0 propan-2-ol	
LC50 (24h)	9714 mg/l (Daphnia magna)
LC50/96h	9640 mg/l (Pimephales promelas)
LOEC (8 days)	1000 mg/l (algae)
111-76-2 2-butoxyethanol	
LC50	1490 mg/l (Lepomis macrochirus (96 h))

- **12.2 Persistence and degradability** Easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxical effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.

(Contd. on page 10)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 9)

· **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1

· **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

· **Transport category** 2

· **Tunnel restriction code** D

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	50-100

· **VOC-CH** 100.00 %

· **VOC-EU** 745.0 g/l

· **Danish MAL Code** 5-3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.

(Contd. on page 11)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 10.09.2013

Version: 13

Revision: 10.09.2013

Trade name: J03140 - JLM Petrol Air Intake Cleaner 500ml PRO

(Contd. of page 10)

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development

· **Contact:** +31 (0)20 201 4495, info@jlm lubricants.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered. ***

GB