

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date FEB 2020

Version number 2

Revision: FEB 2020

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product Identifier:**

Trade name: JLM Petrol E10 Fuel Treatment #J03175

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Product category: PC0 Other

Application of the substance / the mixture: Fuel Additive.

**1.3 Details of the supplier of the safety data sheet:**

Manufacturer / Importer / Supplier:

JLM Lubricants B.V.

Schiphol Boulevard 127

1118BG Schiphol

Tel.: +31 (0) 20 201 4995

Email: info@jlm lubricants.com

www.jlm lubricants.com

Further information obtainable from: Product safety department.

**1.4 Emergency telephone number:**

+31 20 201 4995

This telephone number can be reached during office hours.

**\* SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture:**

Classification according to Regulation (EC) No 1272/2008:



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**2.2 Label elements:**

Labelling according to Regulation (EC) No 1272/2008: The product is classified and labelled according to the CLP regulation.

Hazard pictograms: GHS08

Signal word: Danger

**Hazard-determining components of labelling:**

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromates

**Hazard statements:**

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements:**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards:**

**Results of PBT and vPvB assessment:**

PBT: Not applicable.

vPvB: Not applicable.

**\* SECTION 3: Composition/information on ingredients**

**3.2 Chemical characterisation: Mixtures:**

Description: Mixture of substances listed below, possibly with non-hazardous additions.

Components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromates ⚠ Asp. Tox. 1, H304	50-100%
CAS: 64742-94-5 EC number: 918-811-1 Index number: 649-424-00-3	Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.] ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	2.5-10%

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: **JLM Petrol E10 Fuel Treatment 250ml**

(Contd. of page 1)

Polymer Reg.nr.: Conf0621	Polyolefin alkyl phenol alkyl amine ⚠ Skin Irrit. 2, H315	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336	≤2.5%
CAS: 91-20-3 EINECS: 202-049-5 Index number: 601-052-00-2 Reg.nr.: Compliant	naphthalene ⚠ Carc. 2, H351; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	<1%
CAS: 25340-17-4 EINECS: 246-874-9	diethylbenzene ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315	<1%
CAS: 104-76-7 EINECS: 203-234-3 Reg.nr.: 01-2119487289-20	2-Ethyl-1-hexanol ⚠ Acute Tox. 3, H331; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1%

**Additional information:** For the wording of the listed hazard phrases See section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures:

#### General information:

Persons, providing assistance, should avoid exposure and danger for themselves or others.

Take affected persons out of danger area and lay down.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation:

Remove the victim into fresh air, and keep at rest in a position that facilitates breathing.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

#### After skin contact:

Take off contaminated clothing immediately and wash the skin with plenty of water (possibly showering).

Do NOT use solvents or thinners.

#### After eye contact:

If possible, remove contact lenses.

Rinse opened eye for several minutes (at least 15 minutes) under running water. If symptoms persist, consult a doctor.

**After ingestion:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed:** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed:**

After ingestion of the liquid, droplets of the product may enter the lungs (aspiration), whereby pneumonia can occur.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media:

**Suitable extinguishing agents:** CO<sub>2</sub>, powder, foam or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### 5.2 Special hazards arising from the substance or mixture:

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

Keep dust/vapour clouds away from possible ignition points.

### 5.3 Advice for firefighters:

**Protective equipment:** Wear self-contained respiratory protective device.

**Additional information:** Cool endangered tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Avoid breathing vapor and contact with eyes, skin and clothing.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 3)

— GB —

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: JLM Petrol E10 Fuel Treatment 250ml

(Contd. of page 2)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Observe the general rules for fire prevention.

**7.2 Conditions for safe storage, including any incompatibilities:** Storage must comply with the local regulations.

### Storage:

#### Requirements to be met by storerooms and tanks:

Store only in the original receptacle.

Keep in a cool, dry place, protected from direct sunlight.

All hazardous products must be placed above a sump pallet.

**Information about storage in one common storage facility:** Store away from oxidising agents.

#### Further information about storage conditions:

Protect from heat and direct sunlight.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s):** No further relevant information available.

## \* SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see section 7.

### 8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:		
<b>64742-94-5 Hydrocarbons C10, Aromatics, &lt;1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]</b>		
HSPA (EU)	Short-term value: 151 (8h)	
<b>91-20-3 naphthalene</b>		
IOELV (EU)	Long-term value: 30 mg/m <sup>3</sup> , 10 ppm	
<b>104-76-7 2-Ethyl-1-hexanol</b>		
WEL (Great Britain)	Long-term value: 5.4 mg/m <sup>3</sup> , 1 ppm	
IOELV (EU)	Long-term value: 5.4 mg/m <sup>3</sup> , 1 ppm	
<b>DNELs</b>		
<b>64742-94-5 Hydrocarbons C10, Aromatics, &lt;1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]</b>		
Oral	Long-term - systemic effects	7.5 mg/kg bw/day (Consumer)
Dermal	Long-term - systemic effects	7.5 mg/kg bw/day (Consumer)
		12.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects	32 mg/m <sup>3</sup> (Consumer)
		151 mg/m <sup>3</sup> (Worker)
<b>91-20-3 naphthalene</b>		
Dermal	Long-term - systemic effects	3.57 mg/kg bw/day (Worker)
Inhalative	Long-term - local effects	25 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects	25 mg/m <sup>3</sup> (Worker)

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: **JLM Petrol E10 Fuel Treatment 250ml**

(Contd. of page 3)

104-76-7 2-Ethyl-1-hexanol		
Oral	Long-term - systemic effects	1.1 mg/kg bw/day (Consumer)
Dermal	Long-term - systemic effects	11.4 mg/kg bw/day (Consumer)
Inhalative	Long-term - systemic effects	23 mg/kg bw/day (Worker)
		2.3 mg/m3 (Consumer)
	Acute - local effects	53.2 mg/m3 (Worker)
		53.2 mg/m3 (Consumer)
		106.4 mg/m3 (Worker)
PNECs		
91-20-3 naphthalene		
Fresh water		0.0024 mg/l
Marine water		0.00024 mg/l
STP		2.9 mg/l
Fresh water sediment		0.0672 mg/kg
Marine sediment		0.0672 mg/kg
Soil		0.0533 mg/kg
104-76-7 2-Ethyl-1-hexanol		
Fresh water		0.017 mg/l
Marine water		0.0017 mg/l
Intermittent releases		0.17 mg/l
Fresh water sediment		0.28 mg/kg
Marine sediment		0.028 mg/kg
Soil		0.047 mg/kg
Sewage treatment		10 mg/l

**Additional information:** The lists valid during the making were used as basis.

#### 8.2 Exposure controls

##### Personal protective equipment:

##### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

##### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

##### Protection of hands:



Protective gloves

Use protective gloves to EN ISO 374-1

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

##### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Gloves made of Nitrile rubber, NBR

##### Penetration time of glove material:

Permeation performance > 30 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

##### Eye protection:

Use safety glasses that meets the requirements of EN 166; latest versions.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: JLM Petrol E10 Fuel Treatment 250ml

(Contd. of page 4)



Tightly sealed goggles

**Body protection:** Anti-static clothing**Limitation and supervision of exposure into the environment:** Prevent spills from reaching surface waters or soil.

#### \* SECTION 9: Physical and chemical properties

<b>9.1 Information on basic physical and chemical properties:</b>	
<b>General Information:</b>	
<b>Appearance:</b>	
Form:	Liquid.
Colour:	Transparent
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
<b>Change in condition</b>	
Melting point/freezing point:	Not determined.
Initial boiling point and boiling range:	160 °C
Flash point:	62 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	> 200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
<b>Explosion limits:</b>	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	1 hPa
Density at 20 °C:	0.8172 g/cm <sup>3</sup>
Relative density:	Not determined.
Vapour density:	Not determined.
Evaporation rate:	Not determined.
<b>Solubility in / Miscibility with:</b>	
Water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
<b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
<b>Solvent content:</b>	
Oxidizing properties:	Does not contain oxidizing properties.
<b>9.2 Other information:</b>	No further relevant information available.

#### SECTION 10: Stability and reactivity

**10.1 Reactivity:** Reacts violently with oxidizing agents, strong acids and strong bases.**10.2 Chemical stability:****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**10.3 Possibility of hazardous reactions:** No dangerous reactions known.**10.4 Conditions to avoid:**

Direct sunlight

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: JLM Petrol E10 Fuel Treatment 250ml

(Contd. of page 5)

Heat

Sparks-Open fire

**10.5 Incompatible materials:** Oxidising Agents**10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

## \* SECTION 11: Toxicological information

### 11.1 Information on toxicological effects:

**Acute toxicity:** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Inhalative	LD50 /1h	>302 mg/l (Rat)
------------	----------	-----------------

#### 64742-94-5 Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]

Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
Inhalative	LD50 /1h	590 mg/l (Rat)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rabbit)
Inhalative	LC50/4 h	>10.2 mg/l (Rat)

#### 91-20-3 naphthalene

Oral	LD50	490 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>100 mg/l (Rat)

#### 104-76-7 2-Ethyl-1-hexanol

Oral	LD50	2,049 mg/kg (Rat)
Dermal	LD50	1,970 mg/kg (rbt)
Inhalative	LC50/4 h	2.5 mg/l (Rat)

#### Primary irritant effect:

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.**Serious eye damage/irritation:** Based on available data, the classification criteria are not met.**Respiratory or skin sensitization:** Based on available data, the classification criteria are not met.

#### CMR effects (carcinogenic, mutagenic and reprotoxic):

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reprotoxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

#### Aspiration hazard:

May be fatal if swallowed and enters airways.

## \* SECTION 12: Ecological information

### 12.1 Toxicity:

#### Aquatic toxicity:

#### 64742-94-5 Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]

LL50/96h	677.9 mg/l (Bateria)
	2 mg/l (Oncorhynchus mykiss)
EL50/48H	3 mg/l (Daphnia Magna)

#### 91-20-3 naphthalene

LC50/96h	0.5 mg/l (Fish)
----------	-----------------

#### 104-76-7 2-Ethyl-1-hexanol

LC50/72h	11.5 mg/l (Algae)
LC50/48h	39 mg/l (Daphnia Magna)
LC50/96h	28.2 mg/l (Pimephales promelas)

(Contd. on page 7)

— GB —

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: JLM Petrol E10 Fuel Treatment 250ml

(Contd. of page 6)

**12.2 Persistence and degradability:** No further relevant information available.

**12.3 Bioaccumulative potential:** No further relevant information available.

**12.4 Mobility in soil:** No further relevant information available.

**Ecotoxicological effects:**

**Remark:** Harmful to fish

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment:**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects:** No further relevant information available.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods:**

**Recommendation:** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Contaminated packaging:**

**Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

<b>14.1 UN-Number:</b> ADR/RID/ADN, IMDG, IATA	Void
<b>14.2 UN proper shipping name:</b> ADR/RID/ADN, IMDG, IATA	Void
<b>14.3 Transport hazard class(es):</b> ADR/RID/ADN, IMDG, IATA Class:	Void
<b>14.4 Packing group:</b> ADR/RID/ADN, IMDG, IATA	Void
<b>14.5 Environmental hazards:</b> Marine pollutant:	No
<b>14.6 Special precautions for user:</b>	Not applicable.
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Not applicable.
<b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**Directive 2012/18/EU:**

**Named dangerous substances - ANNEX I:** None of the ingredients are listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII:** Conditions of restriction: 3

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### \* SECTION 16: Other information

**Relevant phrases:**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: FEB 2020

Version number 2

Revision: FEB 2020

### Trade name: JLM Petrol E10 Fuel Treatment 250ml

(Contd. of page 7)

H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
**Training hints:** Take care of good information, instruction and training for users.

**Department issuing SDS:** Environment protection department.

#### Abbreviations and acronyms:

ADN: Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (Division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
EC50: Effective Concentration, 50 percent  
IOELVS: Indicative Occupational Exposure Limit Values  
mPa.s: milliPascal per second  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 3: Acute toxicity - inhalation – Category 3  
Acute Tox. 4: Acute toxicity - inhalation – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Carc. 2: Carcinogenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

#### References:

This information is based on the current available data (suppliers of raw materials, chemistry maps, Annex VI)

See also the internet site: <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>

**Revisions were made in sections marked with \*.**

#### Disclaimer:

The information provided in this Material Safety Data Sheet has been prepared with the utmost care and corresponds to the most recent information available to the supplier on the date of publication mentioned in the header of every page. The contents of this Material Safety Data Sheet should not be considered as a guarantee for certain product properties or fitness for particular purposes. It is the obligation of the user to determine whether the product is suitable for the specific purpose, intended use and the method of application. This Safety Data Sheet only relates to the product described and does not apply to any not defined use or the use of the product in combination with other materials, substances or products. It is the responsibility of the user to use and handle the product with care and to comply with all applicable laws and regulations. The supplier accepts no liability for direct or indirect damages resulting from improper use of this Material Safety Data Sheet and / or the products described therein.