

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** JLM Underbody coating Spray 500ml
- **Article number:** J04603
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Surface protection
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
JLM Lubricants b.v.
Schiphol Boulevard 127
1118 BG Schiphol
The Netherlands
Tel: +31 (0) 20 201 4995
- **6 Further information obtainable from:** Research & Development: info@jlm lubricants.com
- **1.4 Emergency telephone number:** During normal business hours: Tel: +31 (0) 20 2014995

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
-  GHS02 flame
 JLM Underbody coating Spray 500ml
 Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
-  GHS09 environment
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
-  GHS07
 Eye Irrit. 2 H319 Causes serious eye irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
butanone
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes
1-methoxy-2-propanol

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 1)

Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403 Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

- EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
 • **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

- **Description:** Active substance with propellant

Dangerous components:

CAS: 68920-06-9 EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8))	2.5-<10%
	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8))	1-<2.5%
	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32	Carbon black	0.1-<1%
	substance with a Community workplace exposure limit	
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol	0.1-<1%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319	

-
· **Additional information:**

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

74-98-6 propane

WEL Long-term value: 1800 mg/m³

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 2400 mg/m³
Long-term value: 1900 mg/m³

1333-86-4 Carbon black

WEL Short-term value: 7 mg/m³
Long-term value: 3.5 mg/m³

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 4)

· DNELs		
68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer) 2035 mg/m ³ (Worker)
78-93-3 butanone		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer) 1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer) 600 mg/m ³ (Worker)
Reaction mass of ethylbenzene and xylene		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer) 180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local DNEL Long term-systemic	289 mg/m ³ (Worker) 14.8 mg/m ³ (Consumer) 77 mg/m ³ (Worker)
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes		
Oral	DNEL Long term-systemic	1301 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1377 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	1131 mg/m ³ (Consumer) 5306 mg/m ³ (Worker)
107-98-2 1-methoxy-2-propanol		
Oral	DNEL Long term-systemic	3.3 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	18.1 mg/kg bw/day (Consumer) 50.6 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local DNEL Long term-systemic	553.5 mg/m ³ (Worker) 43.9 mg/m ³ (Consumer) 369 mg/m ³ (Worker)
· PNECs		
Reaction mass of ethylbenzene and xylene		
PNEC Freshwater		0.327 mg/l (Undefined)
PNEC Marine water		0.327 mg/l (Undefined)
PNEC Freshwater sediment		12.46 mg/l(dry weight) (Undefined)
PNEC Soil		2.31 (Undefined)
PNEC Sewage Treatment Plant		6.58 mg/l (Undefined)
PNEC Marine water sediment		12.46 mg/l(dry weight) (Undefined)
107-98-2 1-methoxy-2-propanol		
PNEC Freshwater		10 mg/l (Undefined)
PNEC Freshwater sediment		41.6 mg/l(dry weight) (Undefined)
PNEC Soil		2.47 (Undefined)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 5)

· Ingredients with biological limit values:
78-93-3 butanone

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· Additional Occupational Exposure Limit Values for possible hazards during processing:
110-54-3 n-hexane

WEL	Long-term value: 72 mg/m ³ , 20 ppm
-----	--

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2P2

· Protection of hands:


Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· **Form:** Aerosol
 · **Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** -44.5 °C

· **Flash point:** -97 °C

· **Flammability (solid, gas):** Not applicable.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Not determined.

· Explosion limits:

· **Lower:** 0.7 Vol %

· **Upper:** ~20 Vol %

· **Vapour pressure at 20 °C:** 4700 hPa
Not determined.

· **Density at 20 °C:** 0.784 g/cm³

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not applicable.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

· Solvent content:

· **Organic solvents:** 74.8 %

· **Solids content:** 25.2 %

· **9.2 Other information:** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity:** No further relevant information available.

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions:** No dangerous reactions known.

· **10.4 Conditions to avoid:** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2800 mg/kg (rabbit)
Inhalative	LC50/4 h	>23 mg/l (rat)

78-93-3 butanone

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit) 5000 mg/kg (rbt)

Reaction mass of ethylbenzene and xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes

Oral	LD50	16750 mg/kg (rat)
Dermal	LD50	3350 mg/kg (rat)
Inhalative	LC50/4h	259354 mg/l (rat)

107-98-2 1-methoxy-2-propanol

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/6h	27596 mg/m ³ (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

68920-06-9 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
EC50/48h	3 mg/l (Daphnia magna)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 8)

78-93-3 butanone

LC50/96h	2993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)

Reaction mass of ethylbenzene and xylene

NOEC	1.3 mg/l (Fish)
NOEC (7 day)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)

Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes

NOELR (21d)	3.818 mg/l (Daphnia magna)
NOELR (28d)	2.187 mg/l (Oncorhynchus mykiss)
EL50(48h)	17.06 mg/l (Daphnia magna)
LL50 (96h)	9.776 mg/l (Oncorhynchus mykiss)

107-98-2 1-methoxy-2-propanol

LC50/96h	6812 mg/l (Fish)
EC50/48h	23300 mg/l (Daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 02 99	wastes not otherwise specified
----------	--------------------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, ADN, IMDG, IATA**

UN1950

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 9)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, ADN · IMDG · IATA 	UN1950 AEROSOLS AEROSOLS (Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes), MARINE POLLUTANT AEROSOLS, flammable
--	--

· **14.3 Transport hazard class(es)**

· **ADR**



<ul style="list-style-type: none"> · Class · Label 	2 5F Gases. 2.1
--	--------------------

· **ADN**

<ul style="list-style-type: none"> · ADN/R Class: 	2 5F
---	------

· **IMDG**



<ul style="list-style-type: none"> · Class · Label 	2.1 2.1
--	------------

· **IATA**



<ul style="list-style-type: none"> · Class · Label 	2.1 2.1
--	------------

· **14.4 Packing group**

<ul style="list-style-type: none"> · ADR, IMDG, IATA 	Void
--	------

· **14.5 Environmental hazards:**

<ul style="list-style-type: none"> · Marine pollutant: · Special marking (ADR): 	Product contains environmentally hazardous substances: Yes Symbol (fish and tree) Symbol (fish and tree)
---	---

· **14.6 Special precautions for user**

<ul style="list-style-type: none"> · Danger code (Kemler): · EMS Number: · Stowage Code · Segregation Code 	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
--	---

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 10)

- | | |
|--|--|
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0
Not permitted as Excepted Quantity |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0
Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **National regulations:**
- | Class | Share in % |
|-------|------------|
| NK | 50-<75 |
- **VOC-CH** 74.76 %
 - **VOC-EU** 586.1 g/l
 - **Danish MAL Code** 5-3
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 19.03.2019

Version: 26

Revision: 19.03.2019

Trade name: JLM Underbody coating Spray 500ml

(Contd. of page 11)

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Produktsicherheit

Research & Development

· **Contact: G. Groot**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***

GB