

# MQG 0W-30

1 LITRE	5 LITRE	25 LITRE	205 LITRE
VOL801	VOL802	VOL803	VOL804

## PRODUCT SPECIFICATION

### Description

**Recommended for use in the latest Ford and JLR engine designs for both petrol or diesel engines, requiring a low viscosity grade.**

A mid-SAPS engine oil formulated for use in JLR and Ford's latest technology diesel engines. Can be used in engines specifying low viscosity lubricants. MQG 0w-30 is developed for use in Euro V and VI compliant vehicles with DPF after treatment devices, where engines require a product with the below specifications.

- Improved engine efficiency and fuel economy
- Excellent cold temperature flow rates
- Increased film strength at high temperatures
- Low volatility levels
- Superior thermal stability, improved engine cleanliness

### Performance Levels

Ford WSS-M2C950-A

ACEA C2

STJLR.03.5007

Physical Characteristics	
Viscosity at 100°C, cSt.	9.52
Viscosity at 40°C, cSt.	45.67
Viscosity Index	196
Density at 15.6°C	0.840
Flash Point (Closed), °C	210
TBN, mg/KOH/g	8.0
Pour Point, °C	-48

Figures based on average production values.

TDS Oil MQG 0W-30 - 14.10.19 Issue 3

