

MQH 0W-30 C2

1 LITRE	5 LITRE	25 LITRE
VOL117	VOL118	VOL119

PRODUCT SPECIFICATION

Description

MQH 0W-30 C-2 is a fully synthetic mid-SAPS engine oil formulated to maximise performance and fuel economy for vehicles requiring superior, low viscosity lubrication in hybrid, petrol and diesel engines.

Advanced additive technology provides long-term benefits including reduced wear on critical valve-train components. Developed for use in Euro IV, V and VI compliant vehicles.

- Improved engine efficiency and fuel economy
- Low volatility levels
- Excellent cold starting characteristics to protect against engine wear and reduce engine noise
- Offers improved flow rates at low temperatures and increased film strength at high temperatures
- Improved engine cleanliness
- MQH 0W-30 C-2 mid-SAPS oil developed for improved DPF (Diesel Particulate Filter) performance

Performance Levels

ACEA C2

Physical Characteristics	
Viscosity at 100°C, cSt.	9.52
Viscosity at 40°C, cSt.	45.67
Viscosity Index	196
TBN, mg/KOH/g	8.0
Flash Point (Closed), °C	210
Pour Point, °C	-48
Density at 15.6°C	0.840

Figures based on average production values.

TDS Oil MQH 0W-30 C2 - 14.10.19 Issue 3

