

MQS 5W-30 C3

1 LITRE	5 LITRE	25 LITRE	205 LITRE	BULK
VOL170	VOL171	VOL172	VOL173	VOL709

PRODUCT SPECIFICATION

Description

Premium specification fully synthetic mid-SAPS Catalyst Compatible engine oil designed to maximise diesel particulate filter (DPF) and three-way catalyst (TWC) life and improve fuel economy.

MQS 5W-30 is a fully synthetic engine oil, designed to achieve the performance and efficiency demands of modern petrol and diesel engines requiring low viscosity oils. May be used in all VAG vehicles employing fixed service or long life service maintenance schedules where the use of engine oils meeting the requirements of VW 504.00 / 507.00 are specified.

- Improved engine efficiency and fuel economy
- Extended drain period support
- Excellent cold starting characteristics to protect against engine wear and reduce engine noise
- Offers improved flow rates at low temperatures and increased film strength at high temperatures
- High temperature deposit and anti-sludge control
- Low levels of volatility

Performance Levels

ACEA C3

API SN

BMW Longlife-04

MB 229.51

Porsche C30

VW 503.00/503.01/504.00

506.00 / 506.01 / 507.00

Physical Characteristics	
Viscosity at 100°C, cSt.	11.81
Viscosity @ 40°C, cSt.	67.99
Viscosity Index	171
TBN, mg/KOH/g	0.850
Flash Point (Closed), °C	202
Density at 15.6°C	6.5
Pour Point, °C	-42

Figures based on average production values.

TDS Oil MQS 5W-30 C3 - 15.05.18 Issue 3

