

OAT ANTIFREEZE

1 LITRE	2 LITRE	5 LITRE	20 LITRE	205 LITRE
VCA501	VCA502	VCA505	VCA520	VCA5205D1/VCA520D4

PRODUCT SPECIFICATION

Description

Motaquip OAT Anti-Freeze and Summer Coolant uses the latest blend of organic acids and corrosion inhibitors to protect the engine.

Suitable for use in both petrol and diesel engines all year round. This coolant has a five year/100,000 mile life. It meets the performance requirements of most OEM's and national specifications and protects all metals commonly used in engine construction from corrosion and cavitation, including aluminium.

Application

OAT Antifreeze is suitable for use in all climates and provides year round corrosion and freezing protection. When diluted with clean water it can provide freezing protection as low as – 70° C where extreme winters are usual. To ensure satisfactory freeze and corrosion protection it is recommended that the minimum concentration used is 35% by volume. The following freeze protection data should allow the end user to decide the degree of dilution necessary for their situation. Use only clean water to dilute the antifreeze and NEVER use at concentrations greater than 70% by volume.

Performance Levels

BS6580 (1992), ASTM D 3306, ASTM D 4985, Audi TL774-D/F, DAF 74002, Ford WSS-M97B44-D, ISUZU, Renault D, MAN 324-SNF, Jaguar WSS-M97B44-D, Mercedes Benz DBL 7700.30/325.3, MTU: MTL 5048, SAAB 690 1599, SCANIA TB1451, Seat TL774-D/F, Skoda TL774-D/F, Vauxhall QL 130100, Volkswagen TL774-D/F and VOLVO Truck (2006 onwards).

Storage Requirements

The product should be stored at ambient temperatures and periods of exposure to temperatures above 40°C should be minimized. Antifreeze should always be stored in the original container and partly used containers should be closed tightly after use.

Toxicity and Safety

Contains Ethylene glycol. Harmful if swallowed. Keep out of reach of children. For further details see the OAT ANTIFREEZE Safety Data Sheet.

Antifreeze: Water Dilution in % Volume	Freezing Protection, °C
70:30	-70
60:40	-53
50:50	-37
35:65	-19
25:75	-14

TDS Motaquip OAT Antifreeze - 26.04.2013 Issue no. 5

