

## MO0W-20LL

### Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO0W20LL-1	MO0W20LL-4	MO0W20LL-5	MO0W20LL-20	MO0W20LL-60	MO0W20LL-200

## PRODUCT SPECIFICATION

### DESCRIPTION

**MO0W-20LL** is a 100% SYNTHETIC lubricant specially designed for latest generation engines that must meet the Volkswagen 508.00 / 509.00 specifications strongly pushed towards the Fuel Economy and Long-Life philosophies. In fact, MO0W-20LL boasts a very low H.T.H.S. which, combined with its Mid S.A.P.S. nature, guarantees excellent compatibility with post-treatment devices that allow the achievement of Euro VI standards.

**MO0W-20LL** guarantees good compatibility with biofuels for all new engines. All this is combined with great attention to achieving the highest standards of detergency, anti-wear and LSPI that complete the picture of one of the most performing lubricants in the Motaquip range.

### LEVELS OF QUALITY

The lubricant **MO0W-20LL** complies with the following international specifications:

ACEA C5;  
 API SN Plus;  
 GM dexosD;  
 MB229.71;  
 PORSCHE C20;  
 STJLR 51.5122, 03.5006;  
 VW 508.00/509.00;  
 VW TL 52 577

SAE Scale		0W/20
Density at 15°C.Kg/dm <sup>3</sup>	ASTM D1298	0.835
Viscosity at 100°C.cSt	ASTM D445	8.0
Viscosity Index	ASTM D2270	172
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-45
S.A.	ASTM D874	0.80
T.B.N.	ASTM D2896	8.7

The above-mentioned values are indicative of production average values and are not an integral part of the specification