

MO0W-30 Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO0W30-1	MO0W30-4	MO0W30 -5	MO0W30-20	MO0W30-60	MO0W30-200

PRODUCT SPECIFICATION

DESCRIPTION

MO0W-30 is a LONG LIFE 100% synthetic lubricant with low ash content (MID SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

MO0W-30 has been specifically designed to satisfy the latest AUDI-Volkswagen, BMW e Mercedes-Benz specifications for motorizations with prolonged service intervals and fitted with particulate filtration systems, are maintenance-free and without fuel additives

LEVELS OF QUALITY

The lubricant **MO0W-30** complies with the following international specifications:

ACEA C2, C3
API SN/CF
BMW LONG LIFE 04
FIAT 9.55535.DS1, GS1
FORD WSS-M2C950-A
JAGUAR LAND ROVER STJLR.03.5007
MB 229.5
OPEL DEXOS 02
VW 504.00-507.00
PORSCHE C30
RENAULT RN0700, RN0710

SAE Scale		0W/30
Density at 15°C.Kg/dm3	ASTM D1298	0.834
Viscosity at 100°C.cSt	ASTM D445	11.6
Viscosity Index	ASTM D2270	168
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.5

The above-mentioned values are indicative of production average values and are not an integral part of the specification.