

CO10W-30 STOU Heavy Duty Mineral Engine Oil

1 L	4 L	5 L	20 L	60 L	200L	
MO10W30STOU-1	MO10W30STOU-4	MO10W30STOU-5	MO10W30STOU-20	MO10W30STOU-60	MO10W30STOU-200	
PRODUCT SPECIFICATION						

DESCRIPTION

MO10W-30STOU is a multigrade and multifunctional oil of S.T.O.U. type, especially recommended for all types of agricultural diesel engines. The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- An excellent anti-wear capability
- Detergent and dispersant power
- An excellent fluidity at low temperature
- An excellent oxidation resistance

APPLICATIONS

MO10W-30STOU is a multifunctional product to be used in all agriculture and earthmoving systems, whenever a product complying with newer versions of the specification is required. The following benefits can be obtained if you use this product:

- A higher engine cleaning,
- A better protection and longer engine life,
- A good cold start

LEVELS OF QUALITY

The lubricant MO10W-30STOU complies

with the following international specifications:

ACEA E3 API CG-4/SF CNH MAT 3525, 3526 FORD M2C 159B, 159C, 134D; JD J27, J20C, J20D MB 228.1 MF CMD M1135, M1139, M1143, M1144, M1145 NH 82009201, 02, 03 ZF TE-ML 06A, 06B, 07B

SAE Scale		10W/30
Density at 15°C.Kg. /dm3	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	11.5
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	205
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	9

The above-mentioned values are indicative of production average values and are not an integral part of the specification.



TDS Motaquip MO10W-30STOU_REV.2 October 2021