

MO20W-30 U.T.T.O. 80W

Lubricating Oil for Agricultural and Earth Moving Machinery

| 5 L | 20 L | 60 L | 200L |
|------------------|-------------------|-------------------|--------------------|
| MO20W30UTTO80W-5 | MO20W30UTTO80W-20 | MO20W30UTTO80W-60 | MO20W30UTTO80W-200 |

PRODUCT SPECIFICATION

DESCRIPTION

MO20W-30 U.T.T.O. 80W is a multifunctional lubricant (U.T.T.O. – Universal Tractor Transmission Oil) for hydraulic transmissions and systems of earthmoving equipment and agricultural machineries in general. It provides high anti-wear properties, anti-stick and anti-slip properties which allow the best effectiveness of the braking system. The formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit

APPLICATIONS

MO20W-30 U.T.T.O. 80W is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all agricultural machineries and earthmoving equipment, whenever a product with good performance levels is required.

LEVELS OF QUALITY

The lubricant **MO20W-30 U.T.T.O. 80W** complies with the following international specifications:

API GL-4;
ALLISON C4;
CAT TO-2;
John Deere J20C;
Massey-Fergusson M1135

| SAE Scale | | 80W/20W-30 |
|------------------------|------------|------------|
| Density at 15°C.Kg/dm3 | ASTM D1298 | 0.875 |
| Viscosity at 100°C.cSt | ASTM D445 | 10.3 |
| Viscosity Index | ASTM D2270 | 132 |
| Flammability V.A.°C | ASTM D92 | 210 |
| Pour Point °C | ASTM D97 | -24 |

The above-mentioned values are indicative of production average values and are not an integral part of the specification