

MO5W-30D2

Fully Synthetic Dexos2 Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO5W30D2-1	MO5W30D2-4	MO5W30D2-5	MO5W30D2-20	MO5W30D2-60	MO5W30D2-200

PRODUCT SPECIFICATION

DESCRIPTION

MO5W-30D2 is a Long Life 100% synthetic lubricant with mid ash content (Mid SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

MO5W-30D2 has been specifically designed to satisfy the latest ACEA C3 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

LEVELS OF QUALITY

The lubricant **MO5W-30D2** complies with the following international specifications:

ACEA C3
API SN, SM, CF
BMW LONG LIFE 04
FIAT 9.55535.S2, S3
GM DEXOS 02
MB 229.52, 229.51, 229.31, 226.5
PORSCHE C30
PSA B71 2297
VW 502.00, 505.00, 505.01

SAE Scale		5W/30
Density at 15°C.Kg/dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11.8
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	216
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.79
T.B.N.	ASTM D2896	6.8

The above-mentioned values are indicative of production average values and are not an integral part of the specification.