

## MO5W-30LL

### Fully Synthetic Long Life Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO5W30LL-1	MO5W30LL-4	MO5W30LL-5	MO5W30LL-20	MO5W30LL-60	MO5W30LL-200

## PRODUCT SPECIFICATION

### DESCRIPTION

**MO5W-30LL** is a Long Life 100% synthetic Mid SAPS lubricant produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

**MO5W-30LL** has been specifically designed to satisfy the latest AUDI-Volkswagen, BMW e Mercedes-Benz specifications for motorizations with prolonged service intervals and fitted with particulate filtration systems, are maintenance-free and without fuel additives.

### LEVELS OF QUALITY

The lubricant **MO5W-30LL** complies with the following international specifications:

ACEA C2, C3  
API SN, SM, CF  
BMW LONG LIFE 04  
FIAT 9.55535.S3  
FORD WSS-M2C917-A  
MB 226.51, 229.31, 229.51, 229.52  
PORSCHE C30  
VW 504.00-507.00, 505.01, 506.01

SAE Scale		5W/30
Density at 15°C.Kg/dm3	ASTM D1298	0.845
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	165
Flammability V.A.°C	ASTM D92	214
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.2

The above-mentioned values are indicative of production average values and are not an integral part of the specification