

## MO5W-40PD

### Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
MO5W40PD-1	MO5W40PD-4	MO5W40PD-5	MO5W40PD-20	MO5W40PD-60	MO5W40PD-200

## PRODUCT SPECIFICATION

### DESCRIPTION

**MO5W-40PD** is a 100% synthetic MID SAPS lubricant with low ash content produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Furthermore MO5W-40PD has been specifically designed to satisfy the latest ACEA C3 specifications with a mid-ash content and is recommended for engines equipped with particulate filtration systems, maintenance-free and without fuel additives.

### LEVELS OF QUALITY

The lubricant **MO5W-40PD** complies with the following international specifications:

ACEA C3  
 API SN, SM, CF  
 BMW LONG LIFE 04  
 FIAT 9.55535.S2, GH2  
 FORD WSS-M2C 917A  
 GM DEXOS 02  
 MB 226.5, 229.31, 229.51  
 PORSCHE A40  
 PSA B71 2297  
 RENAULT RN0700, RN0710  
 VW 502.00, 505.00, 505.01

SAE Scale		5W/40
Density at 15°C.Kg/dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	13.2
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-33
S.A.	ASTM D874	0.75
T.B.N.	ASTM D2896	7.4

The above-mentioned values are indicative of production average values and are not an integral part of the specification.