

MOATF2

Semi-Synthetic Transmission Fluid

1 L	4 L	5 L	20 L	60 L	200L
MOATF2-1	MOATF2-4	MOATF2-5	MOATF2-20	MOATF2-60	MOATF2-200

PRODUCT SPECIFICATION

DESCRIPTION

MOATF2 is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a DEXRON IID product. It is also used as a hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- Frictional properties,
- Thermal-oxidative stability,
- Wear and corrosion resistance.

Thanks to the above-mentioned typical features it also ensures both a low pour point and a reduced foaming tendency

LEVELS OF QUALITY

The lubricant **MOATF2** complies with the following international specifications:

ALLISON C-4
 CAT TO-2
 FORD MERCON V
 GM DEXRON IID
 MAN 339D
 MB 236.1, 236.7
 FORD MERCON M2C 138CJ
 VOITH 55.6335.32 (G607)
 ZF TE-ML 02F, 03D, 04D, 09A, 11A, 11B, 14A, 17C

Properties		Values
Density at 15°C.Kg/dm3	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-27

The above-mentioned values are indicative of production average values and are not an integral part of the specification.