

MOATF3G

Semi-Synthetic Transmission Fluid

1 L	4 L	5 L	20 L	60 L	200L
MOATF3G-1	MOATF3G-4	MOATF3G-5	MOATF3G-20	MOATF3G-60	MOATF3G-200

PRODUCT SPECIFICATION

DESCRIPTION

MOATF3G is a fluid produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III. It is also used as a hydraulic oil over a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- Frictional properties,
- Thermal-oxidative stability,
- Wear and corrosion resistance,
- Foaming resistance,
- Compatibility with components for automatic transmissions, elastomer seals and plastic parts.

Thanks to the above-mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

LEVELS OF QUALITY

The lubricant **MOATF3G** complies with the following international specifications:

ALLISON C-4
CAT TO-2
FORD MERCON V
GM DEXRON III, IIIG
MB 236.5, 236.9
VOITH G607
ZF TE-ML 02F, 03D, 04D, 09B, 11B, 14A, 17C

Properties		Values
Density at 15°C.Kg/dm3	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-30

The above-mentioned values are indicative of production average values and are not an integral part of the specification.