

ECO H 0W-16

1 LITRE	5 LITRE
VOL909	VOL910

PRODUCT SPECIFICATION

Description

Fuel efficient engine oil

ECO H 0W-16 is a premium synthetic engine oil meticulously designed to meet stringent OEM requirements for low-viscosity oils. It combines synthetic base fluids and advanced additives for superior friction reduction, engine protection, and fuel efficiency. Advances in engine hardware and the 0W-16 classification enhance engine efficiency, reduce fuel consumption, and lower CO2 emissions.

ECO H 0W-16 provides the following benefits:

- Contribution to overall fuel efficiency
- Rapid circulation from cold
- Strong oil film that protects at high temperatures and under arduous work loads
- A high level of component cleanliness and operational efficiency

Applications:

This product is advised for application in engines as per the viscosity and performance requirements outlined in the respective handbooks. It is compatible with vehicles from manufacturers such as Honda, Toyota, Mitsubishi, Nissan, and Suzuki, including models like Baleno (A1K412 SHVS), Ignis (ATK412 & ATK412 SHVS), and Swift (A2LL412 & A2L412 SHVS).

Performance Levels

API SN

Physical Characteristics	
Viscosity @ 100°C, cSt.	6.65
Viscosity @ 40°C, cSt.	33.57
Viscosity Index	159
Density at 15.5°C	0.844
Flash Point (Closed), °C	170
TBN, mg/KOH/g	7.3
Pour Point, °C	-39

Figures based on average production values.

TDS ECO H 0W-16 – 21.04.17 Issue 1

