

ECO V 0W-20

1 LITRE	5 LITRE
VOL913	VOL914

PRODUCT SPECIFICATION

Description

Synthetic technology - fuel efficient

ECO V 0W-20 is a low-viscosity engine oil that offers fuel savings and robust component protection for passenger cars. Its advanced base fluids ensure quick cold starts and promote engine efficiency, while its additives reduce wear and maintain engine cleanliness. Suitable for hybrid vehicles.

ECO V 0W-20 has the following benefits:

- Increased engine efficiency, output and fuel economy
- Rapid cold start flow that reduces noise and wear
- Increased film strength at high temperatures under all driving conditions
- High temperature deposit and anti-sludge control
- Low levels of volatility

Applications:

ECO V 0W-20 is the preferred choice for passenger car engines, including turbocharged models, that necessitate a low viscosity grade meeting one of the performance levels listed below:

Performance Levels

ACEA C5, ACEA C6

API SP, API SN, API SN Plus, API SN RC

ILSAC GF-5

MB 229.71

Fiat 9.55535-GSX

Chrysler MS-12145

Ford WSS-M2C947-B1

Volvo VCC RBSO.2AE

Physical Characteristics	
Viscosity @ 100°C, cSt.	8.4
Viscosity @ 40°C, cSt.	43.6
Viscosity Index	171
Density at 15.6°C	0.844
Flash Point (Closed), °C	207
TBN, mg/KOH/g	7.5
Pour Point, °C	-42

Figures based on average production values.

TDS ECO V 0W-20 – 22.07.21 Issue 2

