

# ECO VA 0W-30

1 LITRE	5 LITRE
VOL941	VOL942

## PRODUCT SPECIFICATION

### Description

#### Synthetic technology - mid-saps

ECO VA 0W-30 is a synthetic technology advanced lubricant, designed for use in the latest engines, including those fitted with exhaust gas after-treatment devices.

ECO VA 0W-30 has the following benefits:

1. Increased engine efficiency.
2. Outstanding fuel economy.
3. Provides extended oil drain capability.
4. Rapid cold start flow that reduces noise and wear.
5. Increased film strength at high temperatures under all driving conditions.
6. High temperature deposit and anti-sludge control.
7. Low levels of volatility.

#### Applications

ECO VA 0W-30 is recommended for the latest petrol and diesel engines, including turbo-charged versions and those fitted with exhaust gas after-treatment devices such as particulate filters, catalytic converters, exhaust gas re-circulation, etc. ECO VA 0W-30 can be used where any of the following manufacturer's specifications are listed.

### Performance Levels

ACEA C3  
 VW 504.00/507.00  
 MB 229.52  
 BMW Longlife 04  
 Porsche C30

Physical Characteristics	
Viscosity @ 100°C, cSt.	11.81
Viscosity @ 40°C, cSt.	67.99
Viscosity Index	171
Density at 15.6°C	0.850
Flash Point (Closed), °C	202
TBN, mg/KOH/g	8.0
Pour Point, °C	-42

Figures based on average production values.

TDS ECO VA 0W-30 – 14.04.23 Issue 1

