

-externally intact, -no mechanical damage, -not dismantled,	Product info sh	eet	Delphi	28540276	
Programming Yes C3 code (20 characters) Unlocking No Adaption values reset No Bleed Yes adjustment at mounting_1 No adjustment at mounting_2 adjustment at mounting_2 Tightening torques Injector/ retainingclamp High Pressure pipe nuts Tightening torques CST Charge terms: e-xternally intact,ro mechanical damage,rot dismantled,	Special tools needed?	No			
Programming Yes C3 code (20 characters) Unlocking No Adaption values reset No Bleed Yes adjustment at mounting_1 No adjustment at mounting_2 adjustment at mounting_2 Tightening torques Injector/ retainingclamp High Pressure pipe nuts Z7 Nm C7 mm Casembly instructions Replace sealing washer Recommendation: replace fuel filter					
Programming Yes C3 code (20 characters) Unlocking No Adaption values reset No Bleed Yes adjustment at mounting_1 No adjustment at mounting_2 adjustment at mounting_2 Tightening torques Injector/ retainingclamp High Pressure pipe nuts Z7 Nm C7 mm Casembly instructions Replace sealing washer Recommendation: replace fuel filter					
Programming Yes C3 code (20 characters) Unlocking No Adaption values reset No Bleed Yes adjustment at mounting_1 No adjustment at mounting_2 adjustment at mounting_2 Tightening torques Injector/ retainingclamp High Pressure pipe nuts Z7 Nm C7 mm Casembly instructions Replace sealing washer Recommendation: replace fuel filter		1			
Unlocking No Adaption values reset No Start 30 sec. with detached connectors adjustment at mounting_1 No Start 30 sec. with detached connectors adjustment at mounting_2 Start 30 sec. with detached connectors adjustment at mounting_2 Start 30 sec. with detached connectors Start 30 sec. Mathematical damage 30 sec. Start 30 sec. 30 sec. Start 30 sec. 30 se	Product specific information				
Adaption values reset No   Bleed Yes   adjustment at mounting_1 No     adjustment at mounting_2     adjustment at mounting_2     Injector/ retainingclamp   High Pressure pipe nuts     27 Nm     Assembly instructions   Replace sealing washer     Replace sealing washer     Core charge terms:   -ot dismantled,	Programming			EMBR00203D	
Adaption values reset No   Bleed Yes   adjustment at mounting_1 No     adjustment at mounting_2     adjustment at mounting_2     Injector/ retainingclamp   High Pressure pipe nuts     27 Nm     Assembly instructions   Replace sealing washer     Replace sealing washer     Core charge terms:   -ot dismantled,	11111			第二章 単元章 の 部128日 Ring 名 本 子 で し こ 2 へ 小 高 数 和 こ 2 中 に こ 2 一 、 4 二 の し 、 、 の い し こ う い し こ う 、 し 、 の い し こ う つ い し こ う つ い し う い し こ う つ い し う い し つ い し う い し つ つ い し つ い つ い し つ つ い し つ い つ つ つ い つ つ つ い つ つ つ つ つ つ つ つ つ つ つ つ つ	
Bleed Yes   adjustment at mounting_1   No     adjustment at mounting_2     adjustment at mounting_2     adjustment at mounting_2     adjustment at mounting_2     Tightening torques   Injector/ retainingclamp   High Pressure pipe nuts     27 Nm     Assembly instructions        Replace sealing washer     Core charge terms:   -externally intact,   -no mechanical damage,   -not dismantled,	Unlocking	No		Declarate C D	
adjustment at mounting_1 No adjustment at mounting_2 adjustment at mounting_2 adjustment at mounting_2 Tightening torques Injector/ retainingclamp High Pressure pipe nuts 27 Nm 27	Adaption values reset	No			
adjustment at mounting_2   adjustment at mounting_2   Injector/ retainingclamp   High Pressure pipe nuts   27 Nm   27 Nm     Assembly instructions   Replace sealing washer     Recommendation: replace fuel filter     Core charge terms:   -no mechanical damage,   -not dismantled,			Start 30 sec. with detac	ched connectors	
Tightening torques   Injector/ retainingclamp   High Pressure pipe nuts   27 Nm   27 Nm   27 Nm     Assembly instructions   Replace sealing washer   Replace sealing washer     Recommendation: replace fuel filter     Core charge terms:   -externally intact,   -no mechanical damage,   -not dismantled,	adjustment at mounting_1	No			
Tightening torques   Injector/ retainingclamp   High Pressure pipe nuts   27 Nm   27 Nm   27 Nm     Assembly instructions   Replace sealing washer   Replace sealing washer     Recommendation: replace fuel filter     Core charge terms:   -externally intact,   -no mechanical damage,   -not dismantled,					
Tightening torques   Injector/ retainingclamp   High Pressure pipe nuts   27 Nm   27 Nm   27 Nm     Assembly instructions   Replace sealing washer   Replace sealing washer     Recommendation: replace fuel filter     Core charge terms:   -externally intact,   -no mechanical damage,   -not dismantled,					
Tightening torques   Injector/ retainingclamp   30 Nm   High Pressure pipe nuts   27 Nm   27 Nm     Assembly instructions   Replace sealing washer   Replace sealing washer     Recommendation: replace fuel filter     Core charge terms:   -externally intact,   -no mechanical damage,   -not dismantled,	adjustment at mounting 2				
Injector/ retainingclamp       30 Nm         High Pressure pipe nuts       27 Nm         27 Nm	,				
Injector/ retainingclamp       30 Nm         High Pressure pipe nuts       27 Nm         27 Nm					
Injector/ retainingclamp       30 Nm         High Pressure pipe nuts       27 Nm         27 Nm					
Injector/ retainingclamp       30 Nm         High Pressure pipe nuts       27 Nm         27 Nm	Tightening torques				
Core charge terms:       -externally intact,         -no mechanical damage,       -not dismantled,	Injector/ retainingclamp				
Replace sealing washer       Recommendation: replace fuel filter         Core charge terms:	High Pressure pipe nuts		27 Nm		
Replace sealing washer       Recommendation: replace fuel filter         Core charge terms:					
Replace sealing washer       Recommendation: replace fuel filter         Core charge terms:					
Replace sealing washer       Recommendation: replace fuel filter         Core charge terms:					
Replace sealing washer       Recommendation: replace fuel filter         Core charge terms:					
Core charge terms:         -externally intact,         -no mechanical damage,         -not dismantled,		1	Assembly instru	ctions	
-externally intact, -no mechanical damage, -not dismantled,	Replace sealing washer		Recomm	nendation: replace fuel filter	
-externally intact, -no mechanical damage, -not dismantled,					
-externally intact, -no mechanical damage, -not dismantled,					
-externally intact, -no mechanical damage, -not dismantled,	Core charge terms:				
-not dismantled,	-externally intact,				
	_				
-no neavy corrosion.	-no heavy corrosion.				