



E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 8/7/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer
Product code : E32PE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Polyol Ester based lubricant with UV dye and performance enhancer for use in air conditioning systems.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Holger Christiansen A/S – A Bosch Group Company

Hedelundvej 13

6705 Esbjerg Ø

Danmark

www.hc-cargo.com

1.4. Emergency telephone number

Emergency number : Holger Christiansen A/S +45 76 14 33 22 (8:00 – 16:00)
USA PHONE:1-800-373-7542, INT'L: 1-484-951-2432
DGA/AAG ENVIRONMENTAL CONTRACT: DGA4000-048

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Reproductive toxicity Category 2 H361
Specific target organ toxicity (repeated exposure) Category 2 H373
Hazardous to the aquatic environment - Chronic Hazard Category 2 H411
Hazardous to the aquatic environment - Chronic Hazard Category 3 H412
Full text of H statements : see section 16


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warning
Hazardous ingredients : phenyl isopropyl phosphate
Hazard statements (CLP) : H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P314 - Get medical advice/attention if you feel unwell.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene	(CAS-No.) 68411-46-1 (EC-No.) 270-128-1	0.1 - 1	Aquatic Chronic 3, H412
phenyl isopropyl phosphate	(CAS-No.) 68937-41-7 (EC-No.) 273-066-3	0.1 - 0.4	Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
-------------------------------	---

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in original container. Keep cool. Keep container closed when not in use. Store in dry protected location to prevent any moisture contact.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

The use of gloves impervious to the specific material handled is advised to prevent skin contact. Suggested protective material: Nitrile, 4.5 mil thickness, tested at 3.5 ml and above with no breakthrough time after 240 minutes.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type P2 - Medium efficiency particle filters may be used.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Color	: Green-yellow.
Odor	: Characteristic.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Unknown.
Log Pow	: No data available
Viscosity, kinematic	: 90 - 110 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene (68411-46-1)

LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male/female, Experimental value, Dermal)

Skin corrosion/irritation : Not classified

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified

Additional information : Based on available data, the classification criteria are not met

Respiratory or skin sensitization : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Additional information : Based on available data, the classification criteria are not met

Specific target organ toxicity – single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Viscosity, kinematic	90 - 110 mm ² /s @ 40°C
----------------------	------------------------------------

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects. Toxic to aquatic life.

Aquatic acute : Not classified

Aquatic chronic : Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene (68411-46-1)

LC50 fish 1	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Experimental value)
-------------	---

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia 1	51 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h algae [mg/l] 1	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Desmodesmus subspicatus, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

phenyl isopropyl phosphate (68937-41-7)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene (68411-46-1)

Persistence and degradability	Contains non readily biodegradable component(s).
-------------------------------	--

12.3. Bioaccumulative potential

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Bioaccumulative potential	Not established.
---------------------------	------------------

phenyl isopropyl phosphate (68937-41-7)

Log Pow	4.9 - 5.2
Bioaccumulative potential	No bioaccumulation data available.

benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene (68411-46-1)

Log Pow	≥ 5 (QSAR, EPIWIN 4.00, 25 °C)
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

benzeneamine,-N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene (68411-46-1)

Ecology - soil	No (test)data on mobility of the components available.
----------------	--

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, strongly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : phenyl isopropyl phosphate, benzeneamine, -N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene are listed

SZW-lijst van mutagene stoffen : phenyl isopropyl phosphate, benzeneamine, -N-phenyl-, reaction product with 2,4,4-trimethylpentene and 2-methylpropene are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

E32PE Ester Refrigeration Lubricant 100 + UV Dye and Performance Enhancer

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-phrases:	
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Repr. 2	Reproductive toxicity Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS EU (REACH Annex II)

This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Tire Seal, Inc. The data on this sheet related only to the specific material designed herein. Tire Seal, Inc. assumes no legal responsibility for the use or reliance upon these data.