

# Safety Data Sheet



according to Regulation (EC) No 1907/2006

## HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

HYDRAULIC OIL ATF DX VI-LV

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Lubricating agent

##### Uses advised against

No information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	BBR Automotive GmbH	
Street:	Mercatorstraße 95	
Place:	D-21502 Geesthacht	
Telephone:	+49 (0)40 600806-0	Telefax: +49 (0)40 600806-10
e-mail:	info@bbr-automotive.de	
Internet:	www.bbr-automotive.de	
Responsible Department:	msds@bbr-automotive.de	

#### 1.4. Emergency telephone number:

Giftnotruf (München)  
+49 (0)89 19240 (24h)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

##### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents / container in accordance with official regulations.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation of base oils and additives.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 2 of 13

### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			43 - < 72,99 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
36878-20-3	Bis(nonylphenyl)amine			0 - < 1,2 %
	253-249-4		01-2119488911-28	
	Aquatic Chronic 4; H413			
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			0 - < 1,2 %
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
	Reaction product of alkylthioalcohol and substituted phosphorus compound			0 - > 0,24 %
	424-820-7		01-0000017126-75	
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H312 H314 H400 H410			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	43 - < 72,99 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
36878-20-3	253-249-4	Bis(nonylphenyl)amine	0 - < 1,2 %	
	oral: LD50 = > 5000 mg/kg			
125643-61-0	406-040-9	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	0 - < 1,2 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg			
	424-820-7	Reaction product of alkylthioalcohol and substituted phosphorus compound	0 - > 0,24 %	
	dermal: LD50 = > 500 mg/kg; oral: LD50 = > 2000 mg/kg M akut; H400: M=10 M chron.; H410: M=10			

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Provide fresh air. Call a doctor if you feel unwell.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 3 of 13

#### **After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### **After ingestion**

Rinse mouth thoroughly with water.

Let water be drunk in little sips (dilution effect).

Do NOT induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- Water spray jet
- alcohol resistant foam.
- Carbon dioxide (CO<sub>2</sub>).
- Extinguishing powder

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Nitrogen oxides (NO<sub>x</sub>)
- Carbon monoxide (CO)
- Carbon dioxide (CO<sub>2</sub>).

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General measures**

Keep people at a distance and stay on the windward side.

Special danger of slipping by leaking/spilling product.

##### **For non-emergency personnel**

Wear protective gloves/protective clothing and eye/face protection.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

## Safety Data Sheet



according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 4 of 13

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

##### **For cleaning up**

Remove from the water surface (e.g. skimming, sucking).

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Avoid formation of oil dust.

Use personal protection equipment.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Clear spills immediately.

##### **Advice on protection against fire and explosion**

No special fire protection measures are necessary.

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed.

Floors should be impervious, resistant to liquids and easy to clean.

##### **Hints on joint storage**

No special measures are necessary.

##### **Further information on storage conditions**

Note Regulation on facilities for the storage, filling and handling water-polluting substances. ...

#### **7.3. Specific end use(s)**

Lubricating agent

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 5 of 13

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
36878-20-3	Bis(nonylphenyl)amine			
Worker DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,62 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,93 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	6,6 mg/m <sup>3</sup>
	Reaction product of alkylthioalcohol and substituted phosphorus compound			
Worker DNEL, long-term		inhalation	systemic	1,76 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,43 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 6 of 13

#### PNEC values

CAS No	Substance	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
36878-20-3	Bis(nonylphenyl)amine	
	Freshwater	0,412 mg/l
	Freshwater (intermittent releases)	1 mg/l
	Marine water	0,041 mg/l
	Freshwater sediment	1 mg/kg
	Marine sediment	0,1 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
	Freshwater	0,018 mg/l
	Freshwater (intermittent releases)	0,018 mg/l
	Marine water	0,002 mg/l
	Freshwater sediment	2 mg/kg
	Marine sediment	0,2 mg/kg
	Secondary poisoning	41,33 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	10 mg/kg
	Reaction product of alkylthioalcohol and substituted phosphorus compound	
	Freshwater	0,0009 mg/l
	Freshwater (intermittent releases)	0,0009 mg/l
	Marine water	0,00009 mg/l
	Freshwater sediment	0,73 mg/kg
	Marine sediment	0,073 mg/kg
	Secondary poisoning	10 mg/kg
	Micro-organisms in sewage treatment plants (STP)	5 mg/l
	Soil	0,086 mg/kg

#### Additional advice on limit values

To date, no national critical limit values exist.

#### 8.2. Exposure controls



#### Protective and hygiene measures

- Take off contaminated clothing and wash it before reuse.
- Wash hands before breaks and after work.
- When using do not eat, drink, smoke, sniff.

# Safety Data Sheet



according to Regulation (EC) No 1907/2006

## HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 7 of 13

### Eye/face protection

During filling, metering, mixing and sampling must be used:  
Wear eye/face protection. DIN EN 166

### Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.  
When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
Tested protective gloves must be worn. EN ISO 374

### Skin protection

Wear suitable protective clothing.

### Respiratory protection

Usually no personal respirative protection necessary.  
In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	red
Odour:	Mineral-oil-like
Odour threshold:	not determined
pH-Value:	not determined

#### Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-48 °C
Flash point:	218 °C

#### Flammability

Solid/liquid:	not applicable
Gas:	not applicable

#### Explosive properties

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Lower explosion limits:	not determined
Upper explosion limits:	not determined

#### Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

#### Oxidizing properties

The product is not: oxidising.

Vapour pressure:	not determined
------------------	----------------

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 8 of 13

Density (at 15 °C): 0,842 g/cm<sup>3</sup>

#### **Solubility in other solvents**

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / kinematic:  
(at 40 °C) 27 mm<sup>2</sup>/s

Relative vapour density: not determined

Evaporation rate: not determined

#### **9.2. Other information**

Solid content: not determined

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

#### **10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

#### **10.3. Possibility of hazardous reactions**

Reaction with: Oxidizing agent

#### **10.4. Conditions to avoid**

Avoid: Thermal decomposition

#### **10.5. Incompatible materials**

Materials to avoid:

- Acids
- Reducing agent
- Oxidising agent

#### **10.6. Hazardous decomposition products**

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO<sub>2</sub>)
- Nitrogen oxides (NO<sub>x</sub>)

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

##### **Acute toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
36878-20-3	Bis(nonylphenyl)amine				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1981)	OECD Guideline 401
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2005)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2000)	OECD Guideline 402
	Reaction product of alkylthioalcohol and substituted phosphorus compound				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 > 500 mg/kg	Rabbit	Study report (1996)	OECD Guideline 402

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.  
Frequently or prolonged contact with skin may cause dermal irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.  
The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
36878-20-3	Bis(nonylphenyl)amine					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Danio rerio (zebrafish)	ECHA Dossier	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2019)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate					
	Acute fish toxicity	LC50 > 0,001 mg/l	96 h	Oncorhynchus mykiss	Study report (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 0 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EL50 110 mg/l	48 h	Daphnia magna	Study report (2000)	OECD Guideline 202
	Fish toxicity	NOEC 0,36 mg/l	33 d	Pimephales promelas	Study report (2009)	OECD Guideline 210
	Crustacea toxicity	NOEC 3,2 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (2000)	OECD Guideline 209
	Reaction product of alkylthioalcohol and substituted phosphorus compound					
	Acute fish toxicity	LC50 1,5 mg/l	96 h			
	Acute algae toxicity	ErC50 0,31 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1996)	EU Method C.3
	Acute crustacea toxicity	EL50 0,09 mg/l	48 h	Daphnia magna	Study report (1996)	EU Method C.2
	Crustacea toxicity	NOEC 0,14 mg/l	21 d	Daphnia magna	Study report (2001)	OECD Guideline 211
	Acute bacteria toxicity	(> 50 mg/l)	3 h	Activated sludge	Study report (1996)	OECD Guideline 209

#### **12.2. Persistence and degradability**

The product has not been tested.

#### **12.3. Bioaccumulative potential**

The product has not been tested.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
36878-20-3	Bis(nonylphenyl)amine	7,6

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 11 of 13

#### BCF

CAS No	Chemical name	BCF	Species	Source
36878-20-3	BIs(nonylphenyl)amine	1584,89	Cyprinus carpio	Study report (2000)
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	38	Cyprinus carpio	Study report (2002)

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

#### 12.6. Endocrine disrupting properties

No information available.

#### 12.7. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

##### 14.1. UN number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

##### 14.1. UN number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### Air transport (ICAO-TI/IATA-DGR)

##### 14.1. UN number:

No dangerous good in sense of this transport regulation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 12 of 13

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

#### **14.7. Maritime transport in bulk according to IMO instruments**

No dangerous good in sense of this transport regulation.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,15,16.

#### **Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### HYDRAULIC OIL ATF DX VI-LV

Product code: 001-10-24897 (1L), 001-10-24898 (5L), 001-10-24899 (20L), 001-10-24900 (60L), 001-10-24901 (208L)

Revision date: 29.04.2023

Page 13 of 13

LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*