

# Safety Data Sheet

according to UK REACH Regulation

## ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Motor oil multigrade

##### Uses advised against

No information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	BBR Automotive GmbH	
Street:	Mercatorstraße 95	
Place:	D-21502 Geesthacht	
Telephone:	+49 (0)40 600806-0	Telefax: +49 (0)40 600806-10
e-mail:	info@bbr-automotive.de	
Internet:	www.bbr-automotive.de	
Responsible Department:	msds@bbr-automotive.de	

#### 1.4. Emergency telephone number:

Giftnotruf (München)  
+49 (0)89 19240 (24h)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

#### 2.2. Label elements

##### Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation of base oils and additives.

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 2 of 11

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			0-90 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
36878-20-3	Blis(nonylphenyl)amine			0 - <3 %
	253-249-4		01-2119488911-28	
	Aquatic Chronic 4; H413			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	0-90 %
	inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
36878-20-3	253-249-4	Blis(nonylphenyl)amine	0 - <3 %
	oral: LD50 = > 5000 mg/kg		

#### Further Information

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down.  
Do not leave affected person unattended.  
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Remove person to fresh air and keep comfortable for breathing.  
In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.  
Take off contaminated clothing and wash it before reuse.  
In case of skin irritation, consult a physician.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth thoroughly with water.  
Let water be drunk in little sips (dilution effect).  
Do NOT induce vomiting.  
In all cases of doubt, or when symptoms persist, seek medical advice.

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 3 of 11

#### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Use water spray jet to protect personnel and to cool endangered containers.  
Co-ordinate fire-fighting measures to the fire surroundings.

- Foam.
- Water spray jet
- Extinguishing powder
- Carbon dioxide (CO<sub>2</sub>).

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO<sub>2</sub>).
- Pyrolysis products, toxic

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep people at a distance and stay on the windward side.  
Special danger of slipping by leaking/spilling product.

##### **For non-emergency personnel**

Wear protective gloves/protective clothing and eye/face protection.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
Do not allow to enter into soil/subsoil.  
Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.  
Remove from the water surface (e.g. skimming, sucking).

# Safety Data Sheet



according to UK REACH Regulation

## ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 4 of 11

### **6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

- Avoid formation of oil dust.
- Use personal protection equipment.
- Do not put any product-impregnated cleaning rags into your trouser pockets.
- Clear spills immediately.

#### **Advice on protection against fire and explosion**

- No special fire protection measures are necessary.
- Take precautionary measures against static discharges.
- Keep away from sources of ignition - No smoking.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

- Keep container tightly closed and in a well-ventilated place.
- Keep only in the original container. Store in a cool dry place.
- Floors should be impervious, resistant to liquids and easy to clean.

#### **Hints on joint storage**

- Do not store together with:
  - Materials capable of ignition under almost all normal temperature conditions
  - Explosives

### **7.3. Specific end use(s)**

Motor oil multigrade

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 5 of 11

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
36878-20-3	BIs(nonylphenyl)amine			
Worker DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
36878-20-3	BIs(nonylphenyl)amine	
Freshwater		0,412 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,041 mg/l
Freshwater sediment		1 mg/kg
Marine sediment		0,1 mg/kg

#### Additional advice on limit values

To date, no national critical limit values exist.

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

##### Eye/face protection

During filling, metering, mixing and sampling must be used:

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 6 of 11

Wear eye/face protection. EN 166

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	light yellow
Odour:	characteristic
Odour threshold:	not determined

	<b>Test method</b>
pH-Value:	not applicable

#### Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	> 280 °C
Pour point:	-51 °C ASTM D 97
Flash point:	226 °C ASTM D 92

#### Flammability

Solid/liquid:	not applicable
Gas:	not applicable

#### Explosive properties

The product is not: Explosive.

Lower explosion limits:	1 vol. %
Upper explosion limits:	10 vol. %
Auto-ignition temperature:	>320 °C
Decomposition temperature:	not determined

#### Oxidizing properties

The product is not: oxidising.

Vapour pressure: (at 20 °C)	<0,005 hPa
--------------------------------	------------

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 7 of 11

Density (at 15 °C): 0,838 g/cm<sup>3</sup> ASTM D 4052  
Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

#### **Solubility in other solvents**

not determined

Partition coefficient n-octanol/water:

log Pow: > 6

Viscosity / dynamic:

not determined

Viscosity / kinematic:  
(at 40 °C)

58,7 mm<sup>2</sup>/s ASTM D 445

Evaporation rate:

not determined

#### **9.2. Other information**

Solid content:

not determined

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

#### **10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

#### **10.3. Possibility of hazardous reactions**

The formation of combustible vapours is possible at temperatures above: Flash point

#### **10.4. Conditions to avoid**

Avoid: Thermal decomposition

#### **10.5. Incompatible materials**

Materials to avoid:

- Oxidising agent, strong

#### **10.6. Hazardous decomposition products**

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO<sub>2</sub>)
- Pyrolysis products, toxic

### SECTION 11: Toxicological information

#### **11.1. Information on hazard classes as defined in GB CLP Regulation**

##### **Acute toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 5,53 mg/l	Rat		OECD Guideline 403
36878-20-3	Bis(nonylphenyl)amine				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1981)	OECD Guideline 401

#### **Irritation and corrosivity**

Based on available data, the classification criteria are not met.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

### **11.2. Information on other hazards**

#### **Endocrine disrupting properties**

See section: 12.6

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

The product is not: Ecotoxic.

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 9 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
36878-20-3	Bis(nonylphenyl)amine					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Danio rerio (zebrafish)	ECHA Dossier	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2019)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202

#### **12.2. Persistence and degradability**

Not readily biodegradable (according to OECD criteria)

#### **12.3. Bioaccumulative potential**

##### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
36878-20-3	Bis(nonylphenyl)amine	7,6

##### **BCF**

CAS No	Chemical name	BCF	Species	Source
36878-20-3	Bis(nonylphenyl)amine	1584,89	Cyprinus carpio	Study report (2000)

#### **12.4. Mobility in soil**

The product has not been tested.

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No information available.

## SECTION 13: Disposal considerations

### **13.1. Waste treatment methods**

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 10 of 11

#### Land transport (ADR/RID)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

#### 14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

##### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

## Safety Data Sheet

according to UK REACH Regulation

### ENGINE OIL PREMIUM VSX LONGLIFE III 0W-30

Product code: 001-10-31523 (1L), 001-10-31524 (5L), 001-10-31525 (20L), 001-10-31526 (60L), 001-10-31527 (208L)

Revision date: 25.05.2023

Page 11 of 11

UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Regulations concerning the international carriage of dangerous goods by rail  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern  
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.  
H413 May cause long lasting harmful effects to aquatic life.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*