A.Z. Meisterteile Motorenöl MT-7.5V 5W-30

Product number: 11175384

Product description

A.Z. Meisterteile Motorenöl MT-7.5V is a synthetic fuel economy low ash engine oil, perfectly suitable for engines especially with particulate filter (DPF) with unit-injector or common-rail systems.

- Modern high performance oil, minimizes wear by rapid oil circulation, especially in the warm-up phase of the engine, allowing maximum loads and provides high safety reserves
- Offers a very high wear and corrosion protection and enhances the service life of the engine
- Latest additive technology keeps the engine clean, reduces friction and guarantees maximum engine lifetime

Quality Level

ACEA C3 API SN/CF BMW LL-04 MB 229.51, 229.31 Porsche C30 VW 504 00/507 00

Application

A.Z. Meisterteile Motorenöl MT-7.5V can be used in many passenger cars, gasoline and diesel engines with DPF and turbocharger, especially developed for VW group, BMW, Mercedes-Benz and Porsche.

| Property | Test method | A.Z. Meisterteile Motorenöl MT-7.5V 5W-30 |
|-------------------------------------|--------------|---|
| Density @ 15 °C, kg/m3 | DIN 51757 | 854 |
| Flash Point, COC, °C | ISO 2592 | ≥215 |
| Kinematic viscosity @ 40 °C, mm2/s | DIN 51562/T1 | 70,72 |
| Kinematic viscosity @ 100 °C, mm2/s | DIN 51562/T1 | 11,9 |
| Viscosity index | DIN ISO 2909 | 165 |
| Pour Point, °C | DIN ISO 3016 | ≼39 |
| Total Base Number, mg KOH/1 g oil | ASTM D 2896 | 8.1 |
| Sulfate ash, % mass | DIN 51575 | ≤0,8 |
| | | |

| All data are average values and are subject to production-related fluctuations. | | | |
|---|-------------|---|--|
| Technical data are subject to change. Please observe the instructions of the manufacturers! | | | |
| Version 1.0 created 16.08.2023 | Page 1 of 1 | PDS_EN_11175384_A.Z. Meisterteile Motorenöl | |
| | | MT-7.5V 5W-30.docx | |