

Hankook & Company


TECHNICAL DATA SHEET


한국앤컴퍼니 주식회사 286, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494 Korea

> Type No.: EFB 95D23L(Q85) Created : 05.02.2022 Modified : 05.02.2022









PERFORMANCE			CONTAINER		
VOLTAGE(V):	12	V	Group:	D23	D.GRAY
C20(Ah):	70	Ah	Hold Down:	BO	
RC(min):	100	min	Please refer to the cata	og or our website for the det	ails of hold down
CCA(A):	670	EN	types of the battery container.		
Vibration:	V3		COVER		
Endurance:	E3		Туре:	Heat Sealed	D.GRAY
Water consumption:	W4		Polarity:	L	
Technology:	Flooded		Terminals:	Standard	
Grid alloy:	Ca/Ca		Filter:	2 Filters both sides	
WEIGHT AND STD. DIMENSION			HANDLES		
Battery weight(kg):	18,00		Handles:	1 Handle	
Volume acid(l):	3,63			REMARK	
Length(mm):	230				
Width(mm):	172				
Height(mm):	220				
Total Height(mm):	220				
This document includes confi					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by HANKOOK & COMPANY.