

STLC PAO A3/B4 5W-30

Fully synthetic engine oil with applied PAO, suitable for gasoline engines and light duty diesel engines without DPF

APPLICATIONS

- Suitable for passenger cars, RV, light trucks, SUV that run on gasoline engine and light duty diesel engine without DPF.
- Excellent performance in the most severe driving conditions of modern start & stop in city traffic and high-speed on highways.

PROPERTIES

- High performance engine oil using 100% synthetic base oils with PAO and the latest additives technology.
- Rapid oil flow property minimizes engine startup wear that occurs during engine start by immediate oil supply.
- Stable on best driving condition through excellent detergent and dispersant properties.
- Excellent engine protection performance while driving through excellent oxidation stability, anti-wear and corrosion resistance.
- Rapid oil flow property in cold condition assures easy start, good drivability and reduction of fuel consumption when engine starts.

SPECIFICATION

- ACEA A3/B4
- API SL
- MB 229.3/229.5
- BMW LL-01
- GM-LL-B-025
- VW 501.01/502.00/505.00

CHARACTERISTICS

Test items	Method	Unit	SAE grade 5W-30
Density 15 °C	ASTM D 4052	g/cm ³	0.852
Viscosity 40 °C	ASTM D 445	mm ² /s	69.7
100 °C		(cSt)	11.9
Viscosity index	ASTM D 2270	-	168
Flash point	ASTM D 92	°C	225
Pour point	ASTM D 97	°C	-37

Above characteristics are mean values given as an information..