

PRODUCT DESCRIPTION

ACDelco 0W-30 C2 is a full synthetic engine oil developed to meet the Ford requirement "WSS-M2C950-A". It is designed to provide long engine life and outstanding protection for diesel engines in a wide range of passenger and light commercial vehicles. Recommended by ACDelco for use in Toyota vehicles, requiring 0W30 ACEA C2 oil with DPF and D4D technology, and where ACEA C2 specifications are called for.

FEATURES & BENEFITS

ACDelco OW-30 C2 meets the technical requirements according to Ford's standard WSS-M2C950-A, based on the OEM engine tests. The use of this product provides the following benefits:

- Improved fuel economy 1
- Extended life of diesel particulate filter 2
- Enhanced lower temperature properties 3
 - 1. based on 950-A OW-30 spec compared to the 913-D 5W-30 oil
 - 2. based on ACEA C2 requirements
 - 3. based on 0W-30 spec compared to 5W-30 oil

APPLICATIONS

ACDelco OW-30 C2 meets Ford, Toyota, ACEA C2 requirements.













Size (L)

20

208

ACDelco P/N

19380013

(no PN yet)

PROPERTIES AND SPECIFICATIONS

Meets or exceeds the requirements of:

- ACEA A1/B1, A5/B5, C2
- Ford WSS-M2C950-A
- Toyota vehicles requiring OW30 ACEA C2 engine oil with DPF and D4D technology

- Grade SAE 0W-30
- Viscosity Index, ASTM D2270 204
- Density 0.842 @ 15.6 C, g/ml, ASTM D4052
- Kinematic Viscosity @ 100 C, 9.6mm2/s, ASTM D445
- Kinematic Viscosity @ 40 C, 44.7 mm2/s, ASTM D445
- Hi-Temp Hi-Shear Viscosity 2.96 @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683
- Flash Point, Cleveland Open Cup, 232°C, ASTM D92
- Ash, Sulfated, mass% 0.77, ASTM D874
- Total Base Number, 8 mgKOH/g, ASTM D2896
- Pour Point, -42°C, ASTM D97
- Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684 20613

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

