





ACDelco

ACDeld

PRODUCT DESCRIPTION

ACDelco Select 20W-50 is a highly refined, high-performance premium mineral engine oil suitable for naturally aspirated and turbo charged petrol & diesel engines not requiring specific manufacturer approvals. It is also suitable for use in vehicles using LPG fuel and older, higher mileage vehicles.

FEATURES & BENEFITS

- Enhanced wear and corrosion protection
- Thermal and oxidation stability
- Advanced additive system to provide excellent engine cleanliness
- High Performance in High and low temperature conditions
- Broad application field

APPLICATIONS

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist call **1800 ACDelco** or visit **acdelco.com.au**





ENGINEERED FOR PERFORMANCE



ACDelco

ACDelco



PROPERTIES AND SPECIFICATIONS

Recommended for use in applications requiring:

API SL, JASO MA2

ACDelco P/N Size (L) 19375074 5 19375075 20

Properties

- Viscosity, ASTM D445
- 185 cSt @ 40°C
- 20.5 cSt @ 100°C
- Sulfated Ash, 0.8 wt%, ASTM D874
- Pour Point, -33°C, ASTM D97
- Flash Point, 230 °C, ASTM D92
- Density @15.6 °C, 0.89 g/ml, ASTM D4052

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.





For your nearest ACDelco Automotive Parts Stockist call **1800 ACDelco** or visit **acdelco.com.au**

