

ACDelco

LONG LIFE SYNTHETIC 5W-30 dexos1® Gen 2 ENGINE OIL



ENGINEERED FOR PERFORMANCE



PRODUCT DESCRIPTION

ACDelco dexos1® Gen 2 is a high-performance engine oil uniquely designed to complement the exacting requirements of General Motors advanced engine technology.

The Gen 2 upgrade offers optimum engine protection and prevents low speed pre-ignition (LSPI) in modern small displacement turbocharged direct injection petrol engines.

It is also suitable for use in many older General Motors vehicles and other vehicle manufacturers' petrol engines and compatible with additive fuels – LPG, CNG, E85 and Bio Diesel.

FEATURES & BENEFITS

- Excellent high temperature protection under severe operating conditions
- Outstanding protection in vehicles of all ages, outperforming conventional-synthetic blended products
- Excellent protection against engine sludge, rust and corrosion under severe and low-temperature operating conditions
- Optimum viscosity and fluidity across a broad range of temperatures
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown
- Controls oil consumption and loss
- API SN Resource Conserving

APPLICATIONS

ACDelco dexos1® Gen 2 is General Motors and Holden service fill for petrol-powered engines and must be used in Holden petrol turbo engines. It also replaces GM-LL-A-025 specification.

Recommended by ACDelco for use in;

- Petrol-powered vehicles and light duty trucks requiring an API SN, SM, SL, SJ or SP.
- Meets ILSAC GF-6 (Starburst Certification Symbol)
- Classified by The American Petroleum Institute (API) as "Resource Conserving" engine lubricants and meets or exceeds ILSAC GF-6.
- Backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit **acdelco.com.au**

ACDelco

ACDelco

LONG LIFE SYNTHETIC 5W-30 dexos1® Gen 2 ENGINE OIL



ENGINEERED FOR PERFORMANCE



PROPERTIES AND SPECIFICATIONS

General Motors and Holden Service Fill dexos1®
(license number D10312HD015)

Approvals:

- dexos1®

Meets or exceeds the requirements of:

- API SP, SN Plus, SN, SM, SL, SJ, ILSAC GF-5 / GF-6

Properties

- Grade SAE 5W-30
- Cold-Cranking Simulator, Apparent Viscosity @ -30 °C, 5,000 mPa.s, ASTM D5293
- Density @ 15 °C, g/ml, ASTM D4052 0.852
- Flash Point, Cleveland Open Cup, 212 °C, ASTM D92
- Kinematic Viscosity @ 100 °C, 10.5 mm²/s, ASTM D445
- Kinematic Viscosity @ 40 °C, 61.1 mm²/s, ASTM D445
- Mini-Rotary Viscometer, Apparent Viscosity, -35 °C, 500 mPa.s, ASTM D4684 20
- Pour Point, -39°C, ASTM D97
- Viscosity Index, ASTM D2270 162

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



| ACDelco P/N | Size (L) |
|-------------|----------|
| 19375065 | 5 |
| 19375066 | 20 |
| 19375067 | 208 |



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit acdelco.com.au

ACDelco