

ACDelco

LONG LIFE SYNTHETIC 5W-30 dexos2®

ENGINE OIL



OILS

ENGINEERED FOR PERFORMANCE



PRODUCT DESCRIPTION

ACDelco dexos2® is a high-performance low ash engine oil engineered for modern diesel engines including those fitted with a diesel particulate filter.

It is also suitable for use in naturally aspirated petrol-powered vehicles.

FEATURES & BENEFITS

- Meets the latest specifications for engine oils required by major vehicle manufacturers with diesel particulate filters and petrol catalytic converters
- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and naturally aspirated petrol vehicles
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown
- Provides excellent fluidity at low temperatures allowing easy winter starting performance and rapid oil circulation
- Excellent performance and long-term engine protection from wear, sludge and deposit build-up

APPLICATIONS

ACDelco dexos2® is General Motors and Holden service fill for most diesel engines fitted with diesel particulate filters and naturally aspirated petrol engines.

Recommended by ACDelco for use in;

- Mercedes-Benz vehicles requiring MB-Approval 229.31 and MB-Approval 229.51
- Ford vehicles requiring WSS-M2C917-A

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist
visit www.acdelco.co.nz or www.acdelco.com.au

ACDelco

ACDelco

LONG LIFE SYNTHETIC 5W-30 dexos2®

ENGINE OIL



OILS

ENGINEERED FOR PERFORMANCE



PROPERTIES & SPECIFICATIONS

General Motors Service Fill dexos2®
(license number D225ACDL815)

Approvals:

- dexos 2®, MB-Approval 229.31, RENAULT RN0700 and RENAULT RN0710

Meets or exceeds the requirements of:

- API SN, SM, SL, ACEA C3

Recommended for use in applications requiring:

- API CF
- Ford WSS-M2C917-A
- MB-Approval 229.31
- MB-Approval 229.51

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



Properties:

- Viscosity, ASTM D 445
- 69 cSt @ 40° C
- 11.9 cSt @ 100° C
- Sulfated Ash, 0.8 wt%, ASTM D 874
- Flash Point, 234 °C, ASTM D 92
- Density @15° C, 0.852 kg/l, ASTM D 4052
- Pour Point, -33 °C, ASTM D 97

ACDelco P/N	Size (L)
19434584	5
19434582	20
19434583	208



For your nearest ACDelco Automotive Parts Stockist
visit www.acdelco.co.nz or www.acdelco.com.au

ACDelco