

# ACDelco

## LONG LIFE SYNTHETIC 5W-30 dexos2® ENGINE OIL



**ENGINEERED FOR PERFORMANCE**



### PRODUCT DESCRIPTION

ACDelco dexos2® is a high-performance low ash engine oil engineered for modern diesel engines including those fitted with a diesel particulate filter.

It is also suitable for use in naturally aspirated petrol-powered vehicles.

### FEATURES & BENEFITS

- Meets the latest specifications for engine oils required by major vehicle manufacturers with diesel particulate filters and petrol catalytic converters
- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and naturally aspirated petrol vehicles
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown
- Provides excellent fluidity at low temperatures allowing easy winter starting performance and rapid oil circulation
- Excellent performance and long-term engine protection from wear, sludge and deposit build-up

### APPLICATIONS

ACDelco dexos2® is General Motors and Holden service fill for most diesel engines fitted with diesel particulate filters and naturally aspirated petrol engines. It also replaces GM-LL-A-025 and GM-LL-B-025.

Recommended by ACDelco for use in;

- Mercedes-Benz vehicles requiring MB-Approval 229.31, MB-Approval 229.51 and MB-Approval 229.52
- BMW vehicles requiring Long-life Oil 04
- Volkswagen vehicles requiring VW 505 00 and VW 505 01
- Ford vehicles requiring WSS-M2C917-A
- Many other European engines meeting Euro 5 standard

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit **acdelco.com.au**

**ACDelco**

# ACDelco

## LONG LIFE SYNTHETIC 5W-30 dexos2® ENGINE OIL



### ENGINEERED FOR PERFORMANCE



#### PROPERTIES & SPECIFICATIONS

General Motors Service Fill dexos2®  
(license number D220AAAF015)

#### Approvals:

- dexos2®

#### Meets or exceeds the requirements of:

- API SN, SM, SL, ACEA C3

#### Recommended for use in applications requiring:

- API CF
- Ford WSS-M2C917-A
- BMW Long-life 04
- MB-Approval 229.31
- MB-Approval 229.51
- MB-Approval 229.52
- Volkswagen (Petrol / Diesel) 505 00 / 505 01

#### HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at [www.acdelco.com.au](http://www.acdelco.com.au)

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



ACDelco P/N	Size (L)
19375048	1
19375049	5
19375050	20
19375051	208

#### Properties:

- Viscosity, ASTM D 445
- 68 cSt @ 40° C
- 11.9 cSt @ 100° C
- Sulfated Ash, 0.8 wt%, ASTM D 874
- Phosphorous 0.08
- Flash Point, 230 °C, ASTM D 92
- Density @15° C, 0.85 kg/l, ASTM D 4052
- Pour Point, -36 °C, ASTM D 97



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit [acdelco.com.au](http://acdelco.com.au)

# ACDelco