

ACDelco

SELECT PLUS SEMI SYNTHETIC 10W40 ENGINE OIL



ENGINEERED FOR PERFORMANCE



PRODUCT DESCRIPTION

ACDelco Select Plus Semi Synthetic 10W40 is a synthetically enhanced premium engine oil for everyday & high-performance engines, in passenger and light commercial vehicles.

It's suitable for vehicles using LPG, petrol and many diesel engines.

FEATURES & BENEFITS

ACDelco Select Plus Semi Synthetic 10W40 is an industry proven product you can trust whilst getting the performance you want from your vehicle.

Select Plus Semi Synthetic 10W40 provides:

- A stay-in-grade lubricant, which maintains its wear protection and fuel economy characteristics even in the most severe conditions.
- Meets the latest API specifications and provides superior performance particularly in the areas of fuel and oil consumption results, high temperature-deposit control and oxidation
- Low oil consumption due to minimum evaporative loss
- Resists oxidation and thermal breakdown even in severe service
- Protection against sludge and deposits
- Provides excellent high temperature protection

APPLICATIONS

ACDelco Select Plus Semi Synthetic 10W40 is formulated to give you confidence of protection beyond that of conventional oils.

Recommended by ACDelco for the following vehicle types and conditions:

- Stop start city driving
- Latest engine technologies
- High Performance engines and turbo chargers
- LPG, petrol and diesel engines
- Passenger and light commercial vehicles
- Highway cruising
- Normal to severe operating conditions

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit **acdelco.com.au**

ACDelco

ACDelco

SELECT PLUS SEMI SYNTHETIC 10W40 ENGINE OIL



ENGINEERED FOR PERFORMANCE



PROPERTIES AND SPECIFICATIONS

Meets or exceeds the requirements of:

- API SN Plus, SN, SM, SL, SJ / CF, ACEA A3/B3

Recommended for use in applications requiring:

- MB-Approval 229.1
- VW 505 00 / VW 501 01

Properties

- Grade SAE 10W-40
- Ash, Sulfated, 0.97 mass%, ASTM D874
- Density 0.869 @ 15 C, g/ml, ASTM D4052
- Flash Point, 220 °C, ASTM D92
- Hi-Temp Hi-Shear Viscosity 4 @ 150 C 1x10(6) sec (-1), cP, CEC L-36-A-90
- Kinematic Viscosity 14.4 @ 100 C, mm²/s, ASTM D445
- Kinematic Viscosity 92 @ 40 C, mm²/s, ASTM D445
- Pour Point, -36 °C, ASTM D97
- Viscosity Index, 154 ASTM D2270
- Total Base Number, mgKOH/g, ASTM D2896 12
- Viscosity Index, ASTM D2270 140 Property

ACDelco P/N	Size (L)
19375052	5
19375053	20
19375054	208

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit acdelco.com.au

ACDelco