

# ACDelco

## SELECT PLUS SEMI SYNTHETIC 10W30 ENGINE OIL



### ENGINEERED FOR PERFORMANCE



#### PRODUCT DESCRIPTION

ACDelco Select Plus Semi Synthetic 10W30 is a synthetically enhanced premium engine oil for everyday & high performance engines, in passenger and light commercial vehicles.

Its suitable for vehicles using LPG, petrol and many diesel engines.

#### FEATURES & BENEFITS

ACDelco Select Plus Semi Synthetic 10W30 is meticulously engineered for today's tougher engine specifications. Ideally suited for driving conditions such as highway driving and lower consistent speed conditions.

ACDelco Select Plus Semi Synthetic 10W30 provides:

- A stay-in-grade lubricant, which maintains its wear protection and fuel economy characteristics even in the most severe conditions
- Low oil consumption due to minimum evaporative loss
- Resists oxidation and thermal breakdown even in severe service
- Provides excellent engine cleanliness

#### APPLICATIONS

ACDelco Select Plus Semi Synthetic 10W30 is formulated to give you confidence of protection beyond that of conventional oils.

ACDelco particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- High Performance engines and turbo chargers
- LPG, petrol and diesel engines
- Passenger and light commercial vehicles
- Highway driving and lower consistent speed conditions

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit **acdelco.com.au**

**ACDelco**



# ACDelco

## SELECT PLUS SEMI SYNTHETIC 10W30 ENGINE OIL



### ENGINEERED FOR PERFORMANCE



#### PROPERTIES AND SPECIFICATIONS

Recommended for use in applications requiring:

API SP, SN Plus, SN, SM, SL, SJ, ILSAC GF-5 / GF-6

##### Properties

- Grade SAE 10W-30
- Ash, Sulfated, 0.8 mass%, ASTM D874
- Density 0.869 @ 15 C, g/ml, ASTM D4052
- Flash Point, 220 °C, ASTM D92
- Hi-Temp Hi-Shear Viscosity 3.2 @ 150 mPa.s, ASTM D4683
- Kinematic Viscosity 10.5 @ 100 C, mm<sup>2</sup>/s, ASTM D445
- Kinematic Viscosity 65.5 @ 40 C, mm<sup>2</sup>/s, ASTM D445
- Pour Point, -36 °C, ASTM D97
- Viscosity Index, 149 ASTM D2270

#### HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at [www.acdelco.com.au](http://www.acdelco.com.au)

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



ACDelco P/N	Size (L)
19375079	5
19375080	20
19375081	208



For your nearest ACDelco Automotive Parts Stockist  
call **1800 ACDelco** or visit **acdelco.com.au**

# ACDelco