



TECHNICAL DATA SHEET

LC 5W-30 LS

Product Type	5W-30 SYNTHETIC LOW SAPS MOTOR OIL
Product Code	N131

Description

A high performance heavy-duty synthetic low SAPS engine oil engineered to offer exceptional fuel saving benefits.

Benefits

- Exceptional fuel saving benefits
- Compatible with after-treatment devices
- Low oil consumption
- Extended oil drain capabilities
- Wide range of applications
- Excellent cold starting properties

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA E6, E7, E9
- API CK-4
- CATERPILLAR ECF-3
- CUMMINS CES 20086
- IVECO 18-1804 TLS E6
- MAN M3777, M3677
- MERCEDES-BENZ MB-228.51, MB-228.31
- RENAULT TRUCKS RLD-3
- SCANIA Low Ash
- VOLVO VDS-4.5



TECHNICAL DATA SHEET

LC 5W-30 LS

Product Type 5W-30 SYNTHETIC LOW SAPS MOTOR OIL
Product Code N131

Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm ² /s	11,7
Viscosity @ 40°C	ASTM D-445	mm ² /s	71
Viscosity Index	ASTM D-2270	-	161,0
Viscosity @-30°C	ASTM D-5293	mPa.s	<6600
Total Base Number	ASTM D-2896	mg/KOH/g	10
Pour Point	ASTM D-5949	°C	-42
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	234

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu