Valvoline Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Revision Date: 26.06.2023 Version: 12.0 Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N2031L CLASSIC 20W50

Motor Oil

Product code 902478

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

Valvoline, Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

•			
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	68784-26-9 272-234-3 01-2119524004-56- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3- DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8 283-392-8 01-2119493626-26- xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 ——— specific concentration limit	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

	Skin Irrit. 2; H315 >= 6.25 % Eye Dam. 1; H318 >= 12.5 % Eye Irrit. 2; H319 >= 10.0 %	
--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

Valvoline... Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion

products

carbon dioxide and carbon monoxide

sulfur oxides

5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Methods for cleaning up

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

Valvoline Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Revision Date: 26.06.2023 Version: 12.0 Print Date: 16/10/2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	Workers	Inhalation	Long-term systemic effects	7.05 mg/m3



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Worker	s Inhalation	Acute systemic effects	167 mg/m3
Worker	s Dermal	Long-term systemic effects	2.08 mg/kg
Worker	s Dermal	Acute systemic effects	80 mg/kg
Consur	ner use Inhalation	Long-term systemic effects	1.74 mg/m3
Consur	ner use Inhalation	Acute systemic effects	0.167 mg/m3
Consur	ner use Dermal	Long-term systemic effects	1.04 mg/kg
Consur	ner use Dermal	Acute systemic effects	40 mg/kg
Consur	ner use Oral	Long-term systemic effects	0.5 mg/kg

Predicted No Effect Concentration (PNEC):

	` ,	
Substance name	Environmental Compartment	Value
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	Sewage treatment plant	100 mg/l
	Marine sediment	3480 mg/kg
	Fresh water sediment	43500 mg/kg
	Soil	8850 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used,



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : $< -30 \, ^{\circ}\text{C}$

Boiling point/boiling range : No data available

Flash point : 260 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Valvoline, Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.878 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : < 9,200 mPa.s (-25 °C)

Viscosity, kinematic : ca. 157 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Heat

10.5 Incompatible materials

Materials to avoid : Alkali metals

aluminum Ammonia

Combustible material

halogens
Metals
metal oxides
Oxidizing agents
peroxides
reducing agents

sodium water

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l

Exposure time: 4 h



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Species : Rabbit

Result : No skin irritation

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit

Result : Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Species : Rabbit

Result : No eye irritation

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Test Type : Human Repeat Insult Patch Testing (HRIPT)

Assessment : Does not cause skin sensitisation.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type : Buehler Test Species : Guinea pig



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Chronic aquatic toxicity : Not classified based on available information.

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

: LC50 (Pimephales promelas (fathead minnow)): > 1.0 mg/l Toxicity to fish

Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Remarks: No toxicity at the limit of solubility

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.0 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

: NOELR (Pseudokirchneriella subcapitata (green algae)): End

point: Growth inhibition Exposure time: 96 h Test Type: static test Test substance: WAF

Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Not classified based on available information. Acute aquatic toxicity

Chronic aquatic toxicity May cause long lasting harmful effects to aquatic life.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS. ZINC SALTS:

Toxicity to daphnia and other : NOEC: 0.4 mg/l

aquatic invertebrates

(Chronic toxicity)

End point: Reproduction Test

Exposure time: 28 d

Species: Daphnia magna (Water flea)

Test substance: WAF

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

12.2 Persistence and degradability

Components:

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: < 10 % Exposure time: 28 d

Method: Modified Sturm Test

Remarks: The toxicological data has been taken from

products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Partition coefficient: n- : log Pow: 9.5

octanol/water

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Partition coefficient: n- : log Pow: 0.56

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Control of Major Accident Hazards Regulations Not applicable

2015 (COMAH)

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

H411 : Toxic to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency: EC-Number - European Community number: ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information: 000000218676

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a



according to Regulation (EC) No. 1907/2006 NAPA® N2031L CLASSIC 20W50 Motor Oil

Version: 12.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN