



TECHNICAL DATA SHEET

5W-30 SS PREMIUM

Product Type 5W-30 SEMI SYNTHETIC MOTOR OIL
Product Code N212

Description

A high performance semi synthetic engine oil suitable for use in a wide variety of modern petrol and diesel engines.

Benefits

- Recommended for use in pre-2009 Ford engines
- Suitable for a wide range of vehicles
- Provides ultimate engine protection for all driving conditions

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA A5/B5, A1/B1
- API SL/CF
- FORD WSS-M2C913-B, WSS-M2C913-A





TECHNICAL DATA SHEET

5W-30 SS PREMIUM

Product Type 5W-30 SEMI SYNTHETIC MOTOR OIL
Product Code N212

Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm ² /s	9,7
Viscosity @ 40°C	ASTM D-445	mm ² /s	54
Viscosity Index	ASTM D-2270	-	170,0
Viscosity @-25°C	ASTM D-5293	mPa.s	3555,0
Total Base Number	ASTM D-2896	mg/KOH/g	12
Pour Point	ASTM D-5949	°C	-45
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	218

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu