

according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier Trade name	:	NAPA® N2225L C2 5W30 LS Synthetic Motor Oil
	Product code	:	902543
1.2	Relevant identified uses of th	e s	ubstance or mixture and uses advised against
	Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3	Details of the supplier of the s	safe	ety data sheet
	Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
	Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
	E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 10 - < 15
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5

For explanation of abbreviations see section 16.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.		
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.		
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.		
4.2 Most important symptoms and effects, both acute and delayed				
Symptoms	:	No symptoms known or expected.		
4.3 Indication of any immediate medical attention and special treatment needed				
Treatment	:	No hazards which require special first aid measures.		
		Treat symptomatically.		

SECTION 5: Firefighting measures

5.1 Extinguishing media					
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.			
Unsuitable extinguishing media	:	High volume water jet			



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023			
5.2 Special hazards arising from the substance or mixture					
Hazardous combustion products	: carbon dioxide and carbon monoxide Nitrogen oxides (NOx)				
5.3 Advice for firefighters					
Special protective equipment for firefighters	: Wear self-contained breathing apparatus necessary.	s for firefighting if			
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are ap circumstances and the surrounding envi				

SECTION 6: Accidental release measures

Personal precautions	:	Refer to protective measures listed in sections 7 and 8.
		Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.
	If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

4/19



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	vision Date: 21.07.2023	Print Date: 16/10/2023			
	Dispose of rinse water ir regulations.	n accordance with local and national			
Advice on protection against fire and explosion	Normal measures for pre	eventive fire protection.			
Hygiene measures	Hygiene measures : Wash hands before breaks and at the end				
7.2 Conditions for safe storage	7.2 Conditions for safe storage, including any incompatibilities				
Requirements for storage areas and containers	: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comp with the technological safety standards.				
Further information on storage stability	No decomposition if stor	ed and applied as directed.			
7.3 Specific end use(s) Specific use(s)	No data available				

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles	
Hand protection Material Break through time Glove thickness Directive	:	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374	
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by	
5 / 10			



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	Revision Date: 21.07.2023 Print Date: 16/10/2023		
	the supplier of the gloves. Also take specific local conditions under which such as the danger of cuts, abrasion The data about break through time/ standard values! The exact break the material has to be obtained from the protective glove. The suitability for a specific workpla with the producers of the protective	n the product is used, n, and the contact time. strength of material are prough time/strength of producer of the ce should be discussed	
Skin and body protection	: Impervious clothing Choose body protection according t concentration of the dangerous sub		
Respiratory protection	: No personal respiratory protective e required.	equipment normally	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 227 °C Method: ASTM D 92
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023
Lower explosion limit / Lower flammability limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: ca. 0.853 g/cm3 (15.6 °C)	
Solubility(ies) Water solubility	: immiscible	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: ca. 54 mm2/s (40 °C)	
Oxidizing properties	: No data available	
9.2 Other information Self-ignition	: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

 Version: 4.0
 Revision Date: 21.07.2023
 Print Date: 16/10/2023

 10.4 Conditions to avoid : None known.

 10.5 Incompatible materials
Materials to avoid
 : Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

,	, , -
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	 LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: The toxicological data has been taken from products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

 Version: 4.0
 Revision Date: 21.07.2023
 Print Date: 16/10/2023

 C14-16-18 Alkyl phenol:
 Acute oral toxicity
 : LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute oral toxicity

 Acute dermal toxicity
 : LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

 Acute dermal toxicity
 : LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

 Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species Result	:	Rabbit
Result	:	No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species Result Remarks	Rabbit Mild skin irritation	
Remarks	The toxicological data has composition.	s been taken from products of similar

C14-16-18 Alkyl phenol:

Method Result	:	OECD Test Guideline 431
Result	:	No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species Result	:	Rabbit
Result	:	No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	: Rabbit
Result	Slight, transient irritation
Species Result Remarks	The toxicological data has been taken from products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

C14-16-18 Alkyl phenol:

Species	:	Rabbit
Result	:	Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment	:	Does not cause skin sensitisation.
	•	

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	: Buehler Test
Species Assessment	: Guinea pig
Assessment	Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species Assessment	Guinea pigDoes not cause skin sensitisation.
Method	: OECD Test Guideline 406
Remarks	: The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assaySpecies: MouseAssessment: The product is a skin sensitiser, sub-category 1B.Method: OECD Test Guideline 429	Test Type	: Local lymph node assay
Assessment : The product is a skin sensitiser, sub-category 1B.	Species	: Mouse
	Assessment	The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 429	Method	OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
-----------------------	--

C14-16-18 Alkyl phenol:

Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

 Liver The substance or mixture is classified as specific target organ
toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

ersion: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023
	Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbo	w trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Acute aquatic toxicity Chronic aquatic toxicity	:	Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

•		
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

C14-16-18 Alkyl phenol:



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

/ersion: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023
Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 100 m Exposure time: 96 h Test Type: static test Test substance: WAF	g/l
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	100 mg/l
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	algae)): > 100 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 2 - 4 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability :	Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B
--------------------	--

C14-16-18 Alkyl phenol:

Biodegradability	:	Result: Re
		Remarks:

Result: Readily biodegradable. Remarks: Expert judgement



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7.5 octanol/water

C14-16-18 Alkyl phenol:

Partition coefficient: n- : log Pow: > 7.2 octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:		
Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.	

SECTION 14: Transport information

14.1 UN number

	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.:	3 Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.4	4 Packing group		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA_P (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (A	An	nex 17)	:	Not applicable
UK REACH Candidate list of sul concern (SVHC) for Authorisatic		tances of very high	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)			:	Not applicable
Regulation (EC) No 1005/2009 deplete the ozone layer	on	substances that	:	Not applicable
UK REACH List of substances s (Annex XIV)	sul	pject to authorisation	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)			Not	applicable
The components of this produ	uc	t are reported in the fo	ollo	wing inventories:
TCSI :	:	On the inventory, or in	con	npliance with the inventory
TSCA :	:	All substances listed as	s ac	tive on the TSCA inventory
AIIC :	:	Not in compliance with	the	inventory
DSL :	:	All components of this	pro	duct are on the Canadian DSL
ENCS :	:	On the inventory, or in	con	npliance with the inventory
KECI :	:	On the inventory, or in	con	npliance with the inventory
		17 / 19		



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0	Revision Date: 21.07.2023	Print Date: 16/10/2023
PICCS	: On the inventory, or in compliance with	h the inventory
IECSC	: On the inventory, or in compliance wit	h the inventory
NZIoC	: Not in compliance with the inventory	

15.2 Chemical safety assessment

No data available

Inventories

STOT RE

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements			
H304	:	May be fatal if swallowed and enters airways.	
H317	:	May cause an allergic skin reaction.	
H373	:	May cause damage to organs through prolonged or repeated exposure.	
H413	:	May cause long lasting harmful effects to aquatic life.	
Full text of other abbreviation	ons		
Aquatic Chronic	:	Long-term (chronic) aquatic hazard	
Asp. Tox.	:	Aspiration hazard	
Skin Sens.	:	Skin sensitisation	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals

: Specific target organ toxicity - repeated exposure



according to Regulation (EC) No. 1907/2006 NAPA® N2225L C2 5W30 LS Synthetic Motor Oil

Version: 4.0

Revision Date: 21.07.2023

Print Date: 16/10/2023

Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information: 000000276452

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN