



TECHNICAL DATA SHEET

C3 5W-30 LS

Product Type	5W-30 SYNTHETIC LOW SAPS MOTOR OIL
Product Code	N223

Description

A high performance low SAPS engine oil suitable for use in a wide variety of modern petrol and diesel engines.

Benefits

- Primarily designed for Vauxhall vehicles requiring Dexos 2 specification
- Provides protection for diesel particulate filters and catalytic converters
- Provides high performance with fuel efficiency
- Long additive lifetime

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA C3
- API SN/CF
- GM Dexos2™
- BMW LONGLIFE-04
- MERCEDES-BENZ MB-229.52, MB-229.51, MB-229.31, MB-226.5
- RENAULT RN0700, RN0710
- VW 505 00/505 01





TECHNICAL DATA SHEET

C3 5W-30 LS

Product Type 5W-30 SYNTHETIC LOW SAPS MOTOR OIL
Product Code N223

Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm ² /s	12,1
Viscosity @ 40°C	ASTM D-445	mm ² /s	72
Viscosity Index	ASTM D-2270	-	165,0
Viscosity @-25°C	ASTM D-5293	mPa.s	<6200
Total Base Number	ASTM D-2896	mg/KOH/g	8
Pour Point	ASTM D-5949	°C	-42
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	230

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu