



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

---

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product identifier**

Trade name : NAPA® N2255L XTR 5W30 LS  
Synthetic Motor Oil

Product code : 901803

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Engine, gear & lubricating oil.

### **1.3 Details of the supplier of the safety data sheet**

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global  
Operations  
Wieldrechtseweg 39  
3316 BG Dordrecht  
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local  
CSR contact person

E-mail address of person : SDS@valvolineglobal.com  
responsible for the SDS

### **1.4 Emergency telephone number**

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number  
at 112

---

## **SECTION 2: Hazards identification**

### **2.1 Classification of the substance or mixture**

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Not a hazardous substance or mixture.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

## 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

### Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 25 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-xxxx	Asp. Tox. 1; H304	>= 5 - < 10
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7 265-174-4 649-477-00-2	Asp. Tox. 1; H304	>= 1 - < 2.5
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
Distillates (petroleum), solvent-	64742-56-9	Asp. Tox. 1; H304	>= 1 - < 2.5



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

dewaxed light paraffinic	265-159-2 649-469-00-9		
C14-16-18 Alkyl phenol	Not Assigned  01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 0.1 - < 0.5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.  
  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Water mist



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Hazardous combustion products : carbon dioxide and carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : For personal protection see section 8.  
Refer to protective measures listed in sections 7 and 8.  
Use personal protective equipment.

**6.2 Environmental precautions**

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

---

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : General industrial hygiene practice.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards.
- Advice on common storage : No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

- Specific use(s) : No data available

---

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Contains no substances with occupational exposure limit values.

**8.2 Exposure controls**

**Personal protective equipment**

- Eye/face protection : Safety glasses
- Hand protection
- Material : neoprene, nitrile rubber
- Break through time :  $\geq 240$  min
- Glove thickness :  $\geq 0.35$  mm



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

Directive	:	Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Skin and body protection	:	Protective suit
Respiratory protection	:	No personal respiratory protective equipment normally required.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	196 °C Method: ASTM D 92
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8534 g/cm <sup>3</sup> (15.6 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	68 mm <sup>2</sup> /s (40 °C) Method: ASTM D 445
Oxidizing properties	:	No data available

## 9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : excessive heat

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg

#### **CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg
---------------------	-----------------------------





## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

Assessment: The substance or mixture has no acute oral toxicity  
Remarks: The toxicological data has been taken from products of similar composition.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: The toxicological data has been taken from products of similar composition.

### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: The toxicological data has been taken from products of similar composition.

### Distillates (petroleum), solvent-dewaxed light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: No mortality observed at this dose.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species	:	Rabbit
Result	:	No skin irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment	:	Slight, transient irritation
Result	:	Slight, transient irritation

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

Result	:	Slight, transient irritation
--------	---	------------------------------

**Reaction products of Benzeneamine, N-phenyl- with nonene (branched):**

Species	:	Rabbit
Result	:	Mild skin irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

**Distillates (petroleum), solvent-dewaxed light paraffinic:**

Species	:	Rabbit
Result	:	Slight, transient irritation

**C14-16-18 Alkyl phenol:**

Method	:	OECD Test Guideline 431
Result	:	No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species	:	Rabbit
Result	:	No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment	:	No eye irritation
Result	:	No eye irritation



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

Result : Slight, transient irritation

**Reaction products of Benzeneamine, N-phenyl- with nonene (branched):**

Species : Rabbit  
Result : Slight, transient irritation  
Remarks : The toxicological data has been taken from products of similar composition.

**Distillates (petroleum), solvent-dewaxed light paraffinic:**

Species : Rabbit  
Result : Slight, transient irritation

**C14-16-18 Alkyl phenol:**

Species : Rabbit  
Result : Slight, transient irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**Reaction products of Benzeneamine, N-phenyl- with nonene (branched):**

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Remarks : The toxicological data has been taken from products of similar composition.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

### Distillates (petroleum), solvent-dewaxed light paraffinic:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406

### C14-16-18 Alkyl phenol:

Test Type	:	Local lymph node assay
Species	:	Mouse
Assessment	:	The product is a skin sensitiser, sub-category 1B.
Method	:	OECD Test Guideline 429

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

### C14-16-18 Alkyl phenol:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - Assessment	:	Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)
------------------------------	---	---

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - Assessment	:	Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)
------------------------------	---	---



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Distillates (petroleum), solvent-dewaxed light paraffinic:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Components:**

**C14-16-18 Alkyl phenol:**

Target Organs : Liver  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

May be fatal if swallowed and enters airways.

**Distillates (petroleum), solvent-dewaxed light paraffinic:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**Further information**

**Product:**

Remarks : No data available

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Toxicity to fish	: LL50 ( <i>Pimephales promelas</i> (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 ( <i>Daphnia magna</i> (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL ( <i>Pseudokirchneriella subcapitata</i> (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic)	: NOELR: >= 1,000 mg/l



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

toxicity)	Exposure time: 14 d Species: <b>Oncorhynchus mykiss (rainbow trout)</b>
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: <b>Daphnia (water flea)</b> Test substance: <b>WAF</b> Method: <b>OECD Test Guideline 211</b>

### Ecotoxicology Assessment

Acute aquatic toxicity	: <b>Not classified based on available information.</b>
Chronic aquatic toxicity	: <b>Not classified based on available information.</b>

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish	: <b>LL50 (Fish): &gt; 100 mg/l</b> Exposure time: <b>96 h</b>
Toxicity to daphnia and other aquatic invertebrates	: <b>EL50 (Aquatic invertebrates): &gt; 10,000 mg/l</b> Exposure time: <b>48 h</b>
Toxicity to algae/aquatic plants	: <b>EL50 (Algae, algal mat (Algae)): &gt; 100 mg/l</b> Exposure time: <b>72 h</b>
Toxicity to fish (Chronic toxicity)	: <b>NOEC: 10 mg/l</b> Species: <b>Fish</b>
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: <b>NOEC: 10 mg/l</b> Species: <b>Aquatic invertebrates</b>

### Ecotoxicology Assessment

Acute aquatic toxicity	: <b>Not classified based on available information.</b>
Chronic aquatic toxicity	: <b>Not classified based on available information.</b>

### CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

### Ecotoxicology Assessment

Acute aquatic toxicity	: <b>Not classified based on available information.</b>
Chronic aquatic toxicity	: <b>Not classified based on available information.</b>



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

### Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

### Distillates (petroleum), solvent-dewaxed light paraffinic:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other	: NOEL: 10 mg/l





## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

aquatic invertebrates (Chronic toxicity)	Exposure time: 21 d Species: <i>Daphnia magna</i> (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211
---	--

### Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

### C14-16-18 Alkyl phenol:

Toxicity to fish	: LC50 ( <i>Cyprinus carpio</i> (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EC50 ( <i>Daphnia magna</i> (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 ( <i>Pseudokirchneriella subcapitata</i> (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

### Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

## 12.2 Persistence and degradability

### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**Reaction products of Benzeneamine, N-phenyl- with nonene (branched):**

Biodegradability : Result: **Not readily biodegradable.**  
Biodegradation: **0 %**  
Exposure time: **28 d**  
Method: **OECD Test Guideline 301B**

**C14-16-18 Alkyl phenol:**

Biodegradability : Result: **Readily biodegradable.**  
Remarks: **Expert judgement**

**12.3 Bioaccumulative potential**

**Components:**

**Reaction products of Benzeneamine, N-phenyl- with nonene (branched):**

Partition coefficient: n- : log Pow: **> 7.5**  
octanol/water

**C14-16-18 Alkyl phenol:**

Partition coefficient: n- : log Pow: **> 7.2**  
octanol/water

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological : No data available



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

information

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA\_P : Not regulated as a dangerous good

### 14.4 Packing group

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

**IATA\_P (Passenger)** : Not regulated as a dangerous good

**14.5 Environmental hazards**

Not regulated as a dangerous good

**14.6 Special precautions for user**

Not applicable

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

**Other regulations:**

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

## 15.2 Chemical safety assessment

No data available

### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

## SECTION 16: Other information

### Full text of H-Statements

H304	: May be fatal if swallowed and enters airways.
H317	: May cause an allergic skin reaction.
H373	: May cause damage to organs through prolonged or repeated exposure.
H413	: May cause long lasting harmful effects to aquatic life.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N2255L XTR 5W30 LS Synthetic Motor  
Oil

Version: 3.0

Revision Date: 29.06.2023

Print Date: 16/10/2023

Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Internal information : 000000279395

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN