

according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name :	NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil
Product code :	903372
1.2 Relevant identified uses of the s	ubstance or mixture and uses advised against
Use of the substance/mixture :	Engine, gear & lubricating oil.
1.3 Details of the supplier of the safe	ety data sheet
Company :	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone :	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person : responsible for the SDS	SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 70 - < 80
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid me	asures
General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	 Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
4.2 Most important symptoms	s and effects, both acute and delayed
Symptoms	: No symptoms known or expected.
4.3 Indication of any immedia	te medical attention and special treatment needed
Treatment	: No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media					
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.			



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023 Print Da	Print Date: 16/10/2023	
Unsuitable extinguishing media	: High volume water jet		
5.2 Special hazards arising from	n the substance or mixture		
Hazardous combustion products	: carbon dioxide and carbon monoxide Nitrogen oxides (NOx)		
5.3 Advice for firefighters			
Special protective equipment for firefighters	 Wear self-contained breathing apparatus for firefig necessary. 	Jhting if	
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate circumstances and the surrounding environment.	to local	

SECTION 6: Accidental release measures

	e equipment and emergency procedures Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.
6.2 Environmental precautions	
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contain	inment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	
See sections: 7, 8, 11, 12 and 13.	

SECTION 7: Handling and storage

7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0		Re	evision Date: 27.07.2023	Print Date: 16/10/2023		
	Advice on safe handling	:	 Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and natio regulations. 			
	Advice on protection against fire and explosion	:	Normal measures for preventive fire prot	ection.		
	Hygiene measures	:	Wash hands before breaks and at the en	d of workday.		
7.2	7.2 Conditions for safe storage, including any incompatibilities					
	Requirements for storage areas and containers	: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must co with the technological safety standards.				
	Further information on storage stability	:	No decomposition if stored and applied a	as directed.		
7.3	Specific end use(s) Specific use(s)	:	No data available			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipm	ent	
Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection		
Material	:	neoprene, nitrile rubber
Break through time	:	>= 240 min
Glove thickness	:	>= 0.35 mm
Directive	:	Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard
		5 / 00



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
	EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemic breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The suitability for a specific workplace should be discusse with the producers of the protective gloves.	
Skin and body protection	: Impervious clothing Choose body protection accord concentration of the dangerous	0
Respiratory protection	: No personal respiratory protecti required.	ive equipment normally

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -48 °C
Boiling point/boiling range	:	No data available
Flash point	:	224 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
		6 / 20



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0		vision Date: 27.07.2023	Print Date: 16/10/2023
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	ca. 0.843 g/cm3 (15.6 °C)	
Solubility(ies) Water solubility	:	insoluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	< 6,000 mPa.s (-35 °C)	
Viscosity, kinematic	:	46.5 mm2/s (40 °C)	
Oxidizing properties	:	No data available	
9.2 Other information			
Self-ignition	:	No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
10.3 Possibility of hazardous	reactions	
Hazardous reactions	: No decomposition if stored and applie	ed as directed.
10.4 Conditions to avoid		
Conditions to avoid	: None known.	
10.5 Incompatible materials		
Materials to avoid	: Strong bases Strong oxidizing agents	

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg

Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
-----------------------	---------------------------

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	 LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):



_

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

GIUNGI		
sion: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed a	at this dose.
Acute dermal toxicity	 LD50 (Rat): > 2,000 mg/kg Assessment: The substance or m toxicity Remarks: The toxicological data h products of similar composition. 	
C14-16-18 Alkyl phenol:		
Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or m toxicity	ixture has no acute oral
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or m toxicity	
Skin corrosion/irritation Not classified based on ava	Remarks: No mortality observed a ailable information.	
Not classified based on ava	ailable information.	
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE)	ailable information. UM), HYDROTREATED HEAVY PARAF	
Not classified based on ava	ailable information.	
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation	
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation	
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED:	
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit	FINIC:
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result Reaction products of Ber Species	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit : No skin irritation nzeneamine, N-phenyl- with nonene (br : Rabbit	FINIC:
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result Reaction products of Ber Species Result	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit : No skin irritation nzeneamine, N-phenyl- with nonene (br : Rabbit : Rabbit : Mild skin irritation	FINIC: ranched):
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result Reaction products of Ber Species	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit : No skin irritation nzeneamine, N-phenyl- with nonene (br : Rabbit	FINIC: ranched):
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result Reaction products of Ber Species Result	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit : No skin irritation nzeneamine, N-phenyl- with nonene (br : Rabbit : Rabbit : Mild skin irritation : The toxicological data has been ta	FINIC: ranched):
Not classified based on ava <u>Components:</u> DISTILLATES (PETROLE) Assessment Result LUBRICATING OILS, PET Species Result Reaction products of Ber Species Result Remarks	ailable information. UM), HYDROTREATED HEAVY PARAF : Slight, transient irritation : Slight, transient irritation TROLEUM, C20-50, HYDROTREATED: : Rabbit : No skin irritation nzeneamine, N-phenyl- with nonene (br : Rabbit : Rabbit : Mild skin irritation : The toxicological data has been ta	FINIC: ranched):



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

Serious eye damage/eye irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment	:	No eye irritation
Result	:	No eye irritation

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

•	
Species	: Rabbit
Result	: Slight, transient irritation
Remarks	: The toxicological data has been taken from products of similar
	composition.

C14-16-18 Alkyl phenol:

Species	:	Rabbit
Result	:	Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment	:	Does not cause skin sensitisation.
Remarks	:	Based on similar product.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

• •		
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Remarks	:	The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Test Type	: Local lymph node assay
Species	: Mouse
	The product is a skin sensitiser, sub-category 1B.OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
		Result: negative

C14-16-18 Alkyl phenol:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

Assessment

(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs	: Liver
Assessment	: The substance or mixture is classified as specific target organ
	toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: No data available



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

SECTION 12: Ecological information

12.1 Toxicity

Product:				
Ecotoxicology Assessment Acute aquatic toxicity	:	Not classified based on available information.		
Chronic aquatic toxicity	:	Not classified based on available information.		
Components:				
DISTILLATES (PETROLEUM). H	IYDROTREATED HEAVY PARAFFINIC:		
Toxicity to fish		LL50 (Fish): > 100 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h		
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h		
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates		
Ecotoxicology Assessment				
Acute aquatic toxicity	:	Not classified based on available information.		
Chronic aquatic toxicity	:	Not classified based on available information.		
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:				
Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test		

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility



_

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
aquatic invertebrates	Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	
Toxicity to algae/aquatic plants	 NOEL (Pseudokirchneriella subcapit 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 	ata (green algae)): >=
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rair	bow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available inf	ormation.
Chronic aquatic toxicity	: Not classified based on available inf	ormation.
Reaction products of Benze	eneamine, N-phenyl- with nonene (bran	ched):
Toxicity to fish	 LC50 (Danio rerio (zebra fish)): > 10 Exposure time: 96 h Test Type: static test Remarks: The toxicological data has products of similar composition. 	-
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)) Exposure time: 48 h Test Type: static test Test substance: WAF	: > 100 mg/l
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapita End point: Growth inhibition Exposure time: 72 h Test Type: static test	ata (algae)): 600 mg/l



_

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023			
Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available informa				
Chronic aquatic toxicity	 Chronic aquatic toxicity Category 4; May cause long lastir harmful effects to aquatic life. 				
C14-16-18 Alkyl phenol:					
Toxicity to fish	 LC50 (Cyprinus carpio (Carp)): > 100 mg Exposure time: 96 h Test Type: static test Test substance: WAF 	Л			
Toxicity to daphnia and other aquatic invertebrates	 EC50 (Daphnia magna (Water flea)): > 10 Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 	ጋ0 mg/l			
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (a End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	algae)): > 100 mg/l			
Ecotoxicology Assessment					
Acute aquatic toxicity	: Not classified based on available informa	tion.			
Chronic aquatic toxicity	: Not classified based on available informa	tion.			
12.2 Persistence and degradabil	ity				
Components:					
LUBRICATING OILS, PETRO	LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:				
Biodegradability	 Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B 				
•	neamine, N-phenyl- with nonene (branched	1):			
Biodegradability	 Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B 				



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
C14-16-18 Alkyl phenol: Biodegradability	: Result: Readily biodegradabl Remarks: Expert judgement	le.
12.3 Bioaccumulative potentia	I	
Components:		
Reaction products of Ben Partition coefficient: n- octanol/water	zeneamine, N-phenyl- with nonen : log Pow: > 7.5	e (branched):
C14-16-18 Alkyl phenol: Partition coefficient: n- octanol/water	: log Pow: > 7.2	
12.4 Mobility in soil No data available		
12.5 Results of PBT and vPvB	assessment	
Product:		
Assessment	to be either persistent, bioacc	ains no components considered cumulative and toxic (PBT), or accumulative (vPvB) at levels of
12.6 Other adverse effects		
Product:		
Endocrine disrupting potential	to REACH Article 57(f) or Co	not contain components e disrupting properties according mmission Delegated regulation ion Regulation (EU) 2018/605 at
Additional ecological information	: No data available	

SECTION 13: Disposal considerations

13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023	
Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways of chemical or used container. Send to a licensed waste management		
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.		

SECTION 14: Transport information

14.1 UN number

	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.3	Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.4	Packing group		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA_P (Passenger)	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable		
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable		
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable		
Regulation (EC) No 1005/2009 on substances that : Not applicable deplete the ozone layer			
UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)			
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not applicable		
The components of this product are reported in the fo	ollowing inventories:		
TCSI : On the inventory, or in	compliance with the inventory		
TSCA : All substances listed a	as active on the TSCA inventory		
AIIC : On the inventory, or in	compliance with the inventory		
DSL : All components of this	product are on the Canadian DSL		



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
ENCS	: On the inventory, or in compliance	with the inventory
KECI	: On the inventory, or in compliance	with the inventory
PICCS	: On the inventory, or in compliance	with the inventory
IECSC	: On the inventory, or in compliance	with the inventory
NZIoC	: Not in compliance with the inventor	y

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H317	:	May cause an allergic skin reaction.
H373	:	May cause damage to organs through prolonged or repeated
		exposure.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic :	Long-term (chronic) aquatic hazard
Asp. Tox. :	Aspiration hazard
Skin Sens. :	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;



according to Regulation (EC) No. 1907/2006 NAPA® N229BK500L FD 0W30 ECO LS Synthetic Motor Oil

Version: 6.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT -Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**

Further information

Internal information : 000000266380

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN