

according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil
Product code	:	903367
1.2 Relevant identified uses of the	e s	ubstance or mixture and uses advised against
Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3 Details of the supplier of the s	safe	ety data sheet
Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

#### 1.4 Emergency telephone number

 $00\mathchar`800\mathchar`825\mathchar`8654\/\ 001\mathchar`859\mathchar`202\mathchar`3865, or contact your local emergency telephone number at 112$ 

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 60 - < 70
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 10 - < 15
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Phenol, dodecyl-, sulfurized,	68784-26-9	Aquatic Chronic 4;	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0 Revision Date: 27.06.2023 Print Date: 16/10/2023 carbonates, calcium salts, overbased 272-234-3 H413 01-2119524004-56-XXXX PHOSPHORODITHIOIC ACID, 84605-29-8 Skin Irrit. 2, H315 >= 1 - < 2.5 MIXED O,O-BIS(1,3-283-392-8 Eye Dam. 1; H318 DIMETHYLBUTYL AND ISO-PR) 01-2119493626-26-Aquatic Chronic 2; ESTERS, ZINC SALTS H411 XXXX specific concentration limit Skin Irrit. 2; H315 >= 6.25 % Eye Dam. 1; H318 >= 12.5 % Eye Irrit. 2; H319 >= 10.0 %

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
4.2 Most important sym	ptoms and effects, both acute and delayed	
Symptoms	: No symptoms known or expected	
4.3 Indication of any im	mediate medical attention and special treatm	nent needed
Treatment	: No hazards which require special	first aid measures.
	Treat symptomatically.	

# **SECTION 5: Firefighting measures**

5.1	Extinguishing media Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
	Unsuitable extinguishing media	:	High volume water jet
5.2	Special hazards arising from Hazardous combustion products		e substance or mixture carbon dioxide and carbon monoxide sulfur oxides
5.3	Advice for firefighters Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures			
Personal precautions	:	Use personal protective equipment.	
6.2 Environmental precautions			
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.	
4 / 22			



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe han	dling :	Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
Advice on protectio fire and explosion	n against :	Normal measures for preventive fire protection.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe	e storage, inc	luding any incompatibilities
Requirements for s areas and containe	-	Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on	:	No decomposition if stored and applied as directed.
storage stability		

#### 7.3 Specific end use(s)

Specific use(s)

: No data available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	Workers	Inhalation	Long-term systemic effects	7.05 mg/m3
	Workers	Inhalation	Acute systemic effects	167 mg/m3
	Workers	Dermal	Long-term systemic effects	2.08 mg/kg
	Workers	Dermal	Acute systemic effects	80 mg/kg
	Consumer use	Inhalation	Long-term systemic effects	1.74 mg/m3
	Consumer use	Inhalation	Acute systemic effects	0.167 mg/m3
	Consumer use	Dermal	Long-term systemic effects	1.04 mg/kg
	Consumer use	Dermal	Acute systemic effects	40 mg/kg
	Consumer use	Oral	Long-term systemic effects	0.5 mg/kg

#### Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	Sewage treatment plant	100 mg/l
	Marine sediment	3480 mg/kg
	Fresh water sediment	43500 mg/kg
	Soil	8850 mg/kg

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection Material Break through time Glove thickness Directive	-	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Remarks	EN 374 derived from it. Glove replaced if there is any indicat breakthrough. Please observe permeability and breakthroug the supplier of the gloves. Als specific local conditions unde such as the danger of cuts, al The data about break through standard values! The exact be material has to be obtained fre protective glove.	EU) 2016/425 and the standard es should be discarded and tion of degradation or chemical e the instructions regarding h time which are provided by so take into consideration the r which the product is used, brasion, and the contact time. n time/strength of material are reak through time/strength of rom the producer of the porkplace should be discussed
Skin and body protection	: Impervious clothing Choose body protection acco concentration of the dangerou	rding to the amount and us substance at the work place.
Respiratory protection	: No personal respiratory prote required.	ctive equipment normally

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 224 °C Method: Cleveland open cup
Evaporation rate	:	No data available
		7 / 22



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Flammability (solid, gas)	: No data available	
Upper explosion limit / Upper flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: ca. 0.857 g/cm3	
Bulk density	: No data available	
Solubility(ies) Water solubility	: insoluble	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: < 6,400 mPa.s (-30 °C)	
Viscosity, kinematic	: ca. 87 mm2/s (40 °C)	
Oxidizing properties	: No data available	
<b>9.2 Other information</b> Self-ignition	: No data available	

### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

<b>10.2 Chemical stability</b> No decomposition if stored and applied as directed.			
10.3 Possibility of hazardous re	eactions		
Hazardous reactions	: No decomposition if stored and applied as directed.		
<b>10.4 Conditions to avoid</b> Conditions to avoid	: excessive heat		
<b>10.5 Incompatible materials</b> Materials to avoid	: Strong oxidizing agents		

#### **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

Not classified based on available information.

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

/ersion: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
DISTILLATES (PETROLEU	IM), SOLVENT-DEWAXED HEAVY PA	RAFFINIC:
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg	
Phenol, dodecyl-, sulfurize	ed, carbonates, calcium salts, overba	sed:
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg	
PHOSPHORODITHIOIC AC ZINC SALTS:	CID, MIXED O,O-BIS(1,3-DIMETHYLBU	ITYL AND ISO-PR) ESTERS,
Acute inhalation toxicity	: LC50 (Rat): > 2.3 mg/l Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or m inhalation toxicity	hixture has no acute
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or m toxicity	nixture has no acute dermal
Skin corrosion/irritation		
Not classified based on ava	ilable information.	
Product:		
Remarks	: May cause skin irritation and/or d	ermatitis.
Components:		
LUBRICATING OILS, PETR	ROLEUM, C20-50, HYDROTREATED:	
Species Result	: Rabbit : No skin irritation	
DISTILLATES (PETROLEU	IM), HYDROTREATED HEAVY PARAF	FINIC:
Assessment Result	Slight, transient irritation Slight, transient irritation	

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment	:	Slight, transient irritation
Result	:	Slight, transient irritation



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
DISTILLATES (PETROLEUM	), SOLVENT-DEWAXED HEAVY PARAFFIN	IC:
Assessment Result	<ul><li>Slight, transient irritation</li><li>Slight, transient irritation</li></ul>	
Phenol, dodecyl-, sulfurized	, carbonates, calcium salts, overbased:	
Species Result	: Rabbit : No skin irritation	
PHOSPHORODITHIOIC ACII ZINC SALTS:	D, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AN	ID ISO-PR) ESTERS,
Species Result	: Rabbit : Irritating to skin.	
Serious eye damage/eye irri		
Not classified based on availa		
Product:		
Result	: No eye irritation	
Remarks	: Vapours may cause irritation to the eyes, and the skin.	respiratory system
Components:		
	DLEUM, C20-50, HYDROTREATED:	
Species Result	: Rabbit : No eye irritation	
i vosuit		
DISTILLATES (PETROLEUM	), HYDROTREATED HEAVY PARAFFINIC:	
Assessment Result	<ul><li>No eye irritation</li><li>No eye irritation</li></ul>	
i Coult		
HYDROTREATED LIGHT PA	RAFFINIC DISTILLATE:	
Assessment Result	<ul> <li>Slight, transient irritation</li> <li>Slight, transient irritation</li> </ul>	
Neoul		
DISTILLATES (PETROLEUM	), SOLVENT-DEWAXED HEAVY PARAFFIN	IC:
Assessment	Slight, transient irritation	
Result	: Slight, transient irritation	

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Species Result	: Rabbit : No eye irritation	

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species Result	:	Rabbit
Result	:	Corrosive

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	: Buehler Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Test Type Species Assessment	: Maximisation Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.
Test Type Assessment	: Human Repeat Insult Patch Testing (HRIPT)
Assessment	Does not cause skin sensitisation.

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
-----------------------	--

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro	: Test Type: Ames test
	Test system: Salmonella typhimurium
	Metabolic activation: with and without metabolic activation
	Result: negative

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### **Reproductive toxicity**

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

#### DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

#### **Further information**

#### Product:

Remarks

: No data available

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

# Product:Ecotoxicology AssessmentAcute aquatic toxicity:Not classified based on available information.Chronic aquatic toxicity:Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

#### **Ecotoxicology Assessment**

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Toxicity to algae/aquatic plants Toxicity to fish (Chronic toxicity)	<ul> <li>EL50 (Algae, algal mat (Algae)): &gt; 100 m Exposure time: 72 h</li> <li>NOEC: 10 mg/l Species: Fish</li> </ul>	g/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Species: Aquatic invertebrates	
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available informa	tion.

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

#### Ecotoxicology Assessment

Chronic aquatic toxicity

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

: Not classified based on available information.

#### DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1.0 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 1.0 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Remarks: No toxicity at the limit of solubility
Toxicity to algae/aquatic	:	NOELR (Pseudokirchneriella subcapitata (green algae)): End



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
plants	point: Growth inhibition Exposure time: 96 h Test Type: static test Test substance: WAF Remarks: No toxicity at the limit	of solubility
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available	e information.
Chronic aquatic toxicity	: May cause long lasting harmful e	effects to aquatic life.
PHOSPHORODITHIOIC ACIE ZINC SALTS:	D, MIXED O,O-BIS(1,3-DIMETHYLBU	UTYL AND ISO-PR) ESTERS,
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0.4 mg/l End point: Reproduction Test Exposure time: 28 d Species: Daphnia magna (Water Test substance: WAF Method: OECD Test Guideline 2	

#### **Ecotoxicology Assessment**

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

#### 12.2 Persistence and degradability

#### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 2 - 4 %
		Exposure time: 28 d
		Method: OECD Test Guideline 301B

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

Biodegradability	: Result: Not readily biodegradable.
<u> </u>	Biodegradation: < 10 %
	Exposure time: 28 d
	Method: Modified Sturm Test
	Remarks: The toxicological data has been taken from
	products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability

Result: Not readily biodegradable. Biodegradation: 1.5 % Exposure time: 28 d Method: OECD Test Guideline 301B

#### 12.3 Bioaccumulative potential

#### **Components:**

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased:

2

· · ·	eu, carbonales, calcium sails, overbaseu.
Partition coefficient: n- octanol/water	: log Pow: 9.5
PHOSPHORODITHIOIC A	CID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS,
Partition coefficient: n-	: log Pow: 0.56

12.4 Mobility in soil

octanol/water

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment	:	This substance/mixture contains no components considered
		to be either persistent, bioaccumulative and toxic (PBT), or
		very persistent and very bioaccumulative (vPvB) at levels of
		0.1% or higher.

#### 12.6 Other adverse effects

Product:		
Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	No data available



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

14.1 UN number

Revision Date: 27.06.2023

Print Date: 16/10/2023

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	<ul> <li>Do not dispose of waste into sewer.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Send to a licensed waste management company.</li> </ul>
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14: Transport information**

14.1 UN number		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA_P (Passenger)	: Not regulated as a dangerous good	

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions	s (Annex 17)	:	Not applicable		
UK REACH Candidate list of concern (SVHC) for Authorisa	, ,	:	Not applicable		
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)			Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		:	Not applicable		
UK REACH List of substances subject to authorisation (Annex XIV)		:	Not applicable		
Control of Major Accident Hazards Regulations			t applicable		
The components of this product are reported in the following inventories:					
TCSI	: On the inventory, or in	n coi	mpliance with the inventory		
TSCA : All substances listed as active on the TSCA inventor					



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
AIIC	: Not in compliance with the inventory	/
DSL	: All components of this product are of	on the Canadian DSL
ENCS	: On the inventory, or in compliance w	with the inventory
KECI	: On the inventory, or in compliance w	vith the inventory
PICCS	: On the inventory, or in compliance w	vith the inventory
IECSC	: On the inventory, or in compliance w	with the inventory
NZIoC	: On the inventory, or in compliance v	vith the inventory

#### 15.2 Chemical safety assessment

No data available

#### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

#### Full text of other abbreviations

Aquatic Chronic Asp. Tox. Eye Dam.	:	Long-term (chronic) aquatic hazard Aspiration hazard Serious eye damage
Skin Irrit.		Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;



according to Regulation (EC) No. 1907/2006 NAPA® N234BK500L 5W40 PREMIUM Synthetic Blend Motor Oil

Version: 13.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Internal information : 000000264676

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN