



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N236BK500L FD 5W20 ECOB
Synthetic Motor Oil

Product code : 903375

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number
at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 70 - < 80
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19-xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned 01-0000019337-66-xxxx	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 3;	>= 0.1 - < 0.25



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

		H412	
--	--	------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No symptoms known or expected.
----------	----------------------------------

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: No hazards which require special first aid measures. Treat symptomatically.
-----------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
------------------------------	--



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned	TWA	10 mg/m3	SUPLR EXP

8.2 Exposure controls

Personal protective equipment



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Eye/face protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection	
Material	: neoprene, nitrile rubber
Break through time	: ≥ 240 min
Glove thickness	: ≥ 0.35 mm
Directive	: Equipment should conform to EN 374
Remarks	: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: No data available
Odour Threshold	: No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

pH	:	Not applicable
Pour point	:	< -39 °C
Boiling point/boiling range	:	No data available
Flash point	:	202 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0.853 g/cm ³ (15.6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 45.1 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Result	:	Mild skin irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Method	:	OECD Test Guideline 431
Result	:	No skin irritation

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Species	:	Rabbit
Result	:	Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result	:	Slight, transient irritation
Remarks	:	Expected based on components.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	:	Rabbit
Result	:	Slight, transient irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Species	:	Rabbit
Result	:	Slight, transient irritation

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Species	:	Rabbit
Result	:	Slight, transient irritation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment : Does not cause skin sensitisation.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Remarks	:	The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Test Type	:	Local lymph node assay
Species	:	Mouse
Assessment	:	The product is a skin sensitiser, sub-category 1B.
Method	:	OECD Test Guideline 429

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs : **Liver**
Assessment : **The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.**

Aspiration toxicity

Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

|| May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (<i>Pimephales promelas</i> (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (<i>Daphnia magna</i> (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (<i>Pseudokirchneriella subcapitata</i> (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

	Test Type: static test
	Test substance: WAF
	Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: $\geq 1,000$ mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

C14-16-18 Alkyl phenol:



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Toxicity to fish	: LC50 (<i>Cyprinus carpio</i> (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (<i>Pseudokirchneriella subcapitata</i> (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Toxicity to fish	: LC50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): 94.8 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (<i>Daphnia magna</i> (Water flea)): 50 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOELR (<i>Pseudokirchneriella subcapitata</i> (green algae)): 4.05 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other	: NOELR: 100 mg/l



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

aquatic invertebrates (Chronic toxicity)	Exposure time: 21 d Species: <i>Daphnia magna</i> (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211
---	--

Ecotoxicology Assessment

Acute aquatic toxicity	: Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

C14-16-18 Alkyl phenol:

Biodegradability	: Result: Readily biodegradable. Remarks: Expert judgement
------------------	---

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 23 % Exposure time: 28 d Method: OECD Test Guideline 301B Remarks: The toxicological data has been taken from products of similar composition.
------------------	---



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-octanol/water : log Pow: > 7.5

C14-16-18 Alkyl phenol:

Partition coefficient: n-octanol/water : log Pow: > 7.2

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Partition coefficient: n-octanol/water : log Pow: > 5.1
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

- | | |
|------------------------|--|
| Product | : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers. |

SECTION 14: Transport information

14.1 UN number

- | | |
|--------|-------------------------------------|
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA_P | : Not regulated as a dangerous good |

14.2 UN proper shipping name

- | | |
|--------|-------------------------------------|
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA_P | : Not regulated as a dangerous good |

14.3 Transport hazard class(es)

- | | |
|--------|-------------------------------------|
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA_P | : Not regulated as a dangerous good |

14.4 Packing group

- | | |
|--------------------|-------------------------------------|
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA (Cargo) | : Not regulated as a dangerous good |
| IATA_P (Passenger) | : Not regulated as a dangerous good |



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
SUPLR EXP	: Supplier-recommended exposure guidelines
SUPLR EXP / TWA	: Time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N236BK500L FD 5W20 ECOB Synthetic
Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000242474

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN