

according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N2361L FD 5W20 ECO B

Synthetic Motor Oil

Product code : 902435

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

## 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl

dithiocarbamate complex. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 70 - < 80
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned 01-0000019337-66- xxxx	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 3;	>= 0.1 - < 0.25



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

H412

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion : carbon dioxide and carbon monoxide

products

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Revision Date: 27.06.2023 Version: 8.0 Print Date: 16/10/2023

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against:

fire and explosion

Normal measures for preventive fire protection.

: Wash hands before breaks and at the end of workday. Hygiene measures

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

### **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned	TWA	10 mg/m3	SUPLR EXP

## 8.2 Exposure controls

### Personal protective equipment



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

pH : Not applicable

Pour point : < -39 °C

Boiling point/boiling range : No data available

Flash point : 202 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.853 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 45.1 mm2/s (40 °C)

Oxidizing properties : No data available

### 9.2 Other information



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Self-ignition : No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

## 10.5 Incompatible materials

Materials to avoid : Strong bases

Strong oxidizing agents

# 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### **Acute toxicity**

Not classified based on available information.

## **Components:**

### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit

Result : No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Result : Mild skin irritation

Remarks : The toxicological data has been taken from products of similar

composition.

C14-16-18 Alkyl phenol:

Method : OECD Test Guideline 431

Result : No skin irritation

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Species : Rabbit

Result : Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Result : Slight, transient irritation

Remarks : Expected based on components.

**Components:** 

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:** 

Species : Rabbit

Result : No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit

Result : Slight, transient irritation

Remarks : The toxicological data has been taken from products of similar

composition.

C14-16-18 Alkyl phenol:

Species : Rabbit

Result : Slight, transient irritation

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Species : Rabbit

Result : Slight, transient irritation



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

# Respiratory or skin sensitisation

### Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

### **Product:**

Assessment : Does not cause skin sensitisation.

### **Components:**

### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

# Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Remarks : The toxicological data has been taken from products of similar

composition.

### C14-16-18 Alkyl phenol:

Test Type : Local lymph node assay

Species : Mouse

Assessment : The product is a skin sensitiser, sub-category 1B.

Method : OECD Test Guideline 429

# Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : The product is a skin sensitiser, sub-category 1B.

### Germ cell mutagenicity

Not classified based on available information.

### **Components:**

### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Components:** 

C14-16-18 Alkyl phenol:

Target Organs : Liver

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

**Aspiration toxicity** 

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

# **Components:**

## LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

### **Further information**

**Product:** 

Remarks : No data available

# **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Product:**

## **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### **Components:**

### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Test Type: static test

Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR >= 1,000 mg/lExposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEL: 10 ma/l

Exposure time: 21 d

Species: Daphnia (water flea)

Test substance: WAF

Method: OECD Test Guideline 211

# **Ecotoxicology Assessment**

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

## Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: The toxicological data has been taken from

products of similar composition.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

## **Ecotoxicology Assessment**

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Chronic aquatic toxicity Category 4; May cause long lasting

harmful effects to aquatic life.

### C14-16-18 Alkyl phenol:



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

> Exposure time: 96 h Test Type: static test Test substance: WAF

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

**Ecotoxicology Assessment** 

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

: LC50 (Oncorhynchus mykiss (rainbow trout)): 94.8 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 50 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: NOELR (Pseudokirchneriella subcapitata (green algae)): 4.05

End point: Growth inhibition Exposure time: 72 h

Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Remarks: The toxicological data has been taken from

products of similar composition.

Toxicity to daphnia and other : NOELR: 100 mg/l



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

aquatic invertebrates Exposure time: 21 d

(Chronic toxicity) Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

12.2 Persistence and degradability

**Components:** 

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol:

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 23 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: The toxicological data has been taken from

products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

# 12.3 Bioaccumulative potential

### **Components:**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7.5

octanol/water

C14-16-18 Alkyl phenol:

Partition coefficient: n- : log Pow: > 7.2

octanol/water

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Partition coefficient: n- : log Pow: > 5.1

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Other adverse effects

**Product:** 

Endocrine disrupting : The substance/mixture does not contain components

potential

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: No data available

## **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

## **SECTION 14: Transport information**

### 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

## 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA\_P : Not regulated as a dangerous good

## 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

## 14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA P (Passenger) : Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

Control of Major Accident Hazards Regulations

2015 (COMAH)

Not applicable

### The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

### 15.2 Chemical safety assessment

No data available

### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### **SECTION 16: Other information**

### **Full text of H-Statements**

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

## Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Skin Irrit. : Skin irritation Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure SUPLR EXP : Supplier-recommended exposure guidelines

SUPLR EXP / TWA : Time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;



according to Regulation (EC) No. 1907/2006 NAPA® N2361L FD 5W20 ECO B Synthetic Motor Oil

Version: 8.0 Revision Date: 27.06.2023 Print Date: 16/10/2023

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

Internal information: 000000242474

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN