

according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b> Trade name :	NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil
Product code :	902394
1.2 Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture :	Engine, gear & lubricating oil.
1.3 Details of the supplier of the sat	fety data sheet
Company :	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone :	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person : responsible for the SDS	SDS@valvolineglobal.com

#### 1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 40 - < 50
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid mea	asures
General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	<ul> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Flush eyes with water as a precaution.</li> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> <li>Take victim immediately to hospital.</li> </ul>
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	: No symptoms known or expected.
4.3 Indication of any immediat	e medical attention and special treatment needed
<b>T</b>	No. 1 and a state of the second state of a first state of the second state of the seco

### Treatment : No hazards which require special first aid measures.

Treat symptomatically.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Revision Date: 19.07.2023 Print D	Date: 16/10/2023
Unsuitable extinguishing media	: High volume water jet	
5.2 Special hazards arising from	the substance or mixture	
Hazardous combustion products	: carbon dioxide and carbon monoxide Nitrogen oxides (NOx)	
5.3 Advice for firefighters		
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firef necessary.	ighting if
Further information	<ul> <li>Standard procedure for chemical fires.</li> <li>Use extinguishing measures that are appropriate circumstances and the surrounding environment.</li> </ul>	

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protectiv	e equipment and emergency procedures
Personal precautions :	Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.
6.2 Environmental precautions	
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for conta	inment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	
See sections: 7, 8, 11, 12 and 13.	

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Re	evision Date: 19.07.2023	Print Date: 16/10/2023
Advice on safe handling	:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be application area. Dispose of rinse water in accordance wit regulations.	
Advice on protection against fire and explosion	:	Normal measures for preventive fire prot	ection.
Hygiene measures	:	Wash hands before breaks and at the er	ld of workday.
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and place. Electrical installations / working m with the technological safety standards.	
Further information on storage stability	:	No decomposition if stored and applied a	as directed.
7.3 Specific end use(s)			
Specific use(s)	:	No data available	

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

Personal protective equipm	ent	
Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection		
Material	:	neoprene, nitrile rubber
Break through time	:	>= 240 min
Glove thickness	:	>= 0.35 mm
Directive	:	Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard
		F / 20



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Revision Date: 19.07.2023	Print Date: 16/10/2023
	EN 374 derived from it. Glove replaced if there is any indicat breakthrough. Please observe permeability and breakthrough the supplier of the gloves. Also specific local conditions under such as the danger of cuts, at The data about break through standard values! The exact br material has to be obtained fro protective glove. The suitability for a specific wo with the producers of the protect	ion of degradation or chemical e the instructions regarding in time which are provided by o take into consideration the which the product is used, orasion, and the contact time. time/strength of material are eak through time/strength of om the producer of the orkplace should be discussed
Skin and body protection	: Impervious clothing Choose body protection accor concentration of the dangerou	rding to the amount and is substance at the work place.
Respiratory protection	: No personal respiratory protect required.	ctive equipment normally

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -39 °C
Boiling point/boiling range	:	No data available
Flash point	:	208 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
		6/20



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Re	vision Date: 19.07.2023	Print Date: 16/10/2023
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	ca. 0.843 g/cm3 (15.6 °C)	
Solubility(ies) Water solubility	:	insoluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	48 mm2/s (40 °C)	
Oxidizing properties	:	No data available	
9.2 Other information			
Self-ignition	:	No data available	

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Revision Date: 19.07.2023	Print Date: 16/10/2023
reactions	
: No decomposition if stored and a	pplied as directed.
: None known.	
: Strong bases Strong oxidizing agents	
	<ul> <li>reactions</li> <li>No decomposition if stored and a</li> <li>None known.</li> <li>Strong bases</li> </ul>

#### **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

### **Components:**

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg

Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
-----------------------	---------------------------

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	<ul> <li>LC50 (Rat): &gt; 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.</li> </ul>
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

aionai		
sion: 7.0	Revision Date: 19.07.2023	Print Date: 16/10/2023
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed	d at this dose.
Acute dermal toxicity	<ul> <li>LD50 (Rat): &gt; 2,000 mg/kg Assessment: The substance or toxicity Remarks: The toxicological data products of similar composition.</li> </ul>	a has been taken from
C14-16-18 Alkyl phenol:		
Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or toxicity	mixture has no acute oral
Acute dermal toxicity	<ul> <li>LD50 (Rat): &gt; 2,000 mg/kg</li> <li>Assessment: The substance or toxicity</li> <li>Remarks: No mortality observed</li> </ul>	
<u>Components:</u> DISTILLATES (PETROLI	EUM), HYDROTREATED HEAVY PARA	
Assessment	: Slight, transient irritation	
Result	: Slight, transient irritation	
LUBRICATING OILS, PE	TROLEUM, C20-50, HYDROTREATED	:
Species Result	: Rabbit : No skin irritation	
Reaction products of Be	nzeneamine, N-phenyl- with nonene (	branched):
Species	: Rabbit	
Result Remarks	<ul> <li>Mild skin irritation</li> <li>The toxicological data has been composition.</li> </ul>	taken from products of similar
C14-16-18 Alkyl phenol:		
Method	: OECD Test Guideline 431	
Result	: No skin irritation	



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

#### Serious eye damage/eye irritation

Not classified based on available information.

#### **Components:**

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment	:	No eye irritation
Result	:	No eye irritation

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No eye irritation

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

•	
Species	: Rabbit
Result	: Slight, transient irritation
Remarks	: The toxicological data has been taken from products of similar
	composition.

#### C14-16-18 Alkyl phenol:

Species	:	Rabbit
Result	:	Slight, transient irritation

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Product:

Assessment	:	Does not cause skin sensitisation.
Remarks	:	Based on similar product.

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species Assessment Method Remarks	<ul> <li>Guinea pig</li> <li>Does not cause skin sensitisation.</li> <li>OECD Test Guideline 406</li> <li>The toxicological data has been taken from products of similar composition.</li> </ul>
	composition.

#### C14-16-18 Alkyl phenol:

Species :	Local lymph node assay Mouse The product is a skin sensitiser, sub-category 1B.
	OECD Test Guideline 429

#### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
		Result: negative

#### C14-16-18 Alkyl phenol:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

#### Carcinogenicity

Not classified based on available information.

**Components:** 

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

Assessment

(EC) 1272/2008, Annex VI, Part 3, Note L)

### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

**Components:** 

#### C14-16-18 Alkyl phenol:

Target Organs	:	Liver
Assessment	:	The substance or mixture is classified as specific target organ
		toxicant, repeated exposure, category 2.

#### Aspiration toxicity

Not classified based on available information.

#### Components:

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

#### **Further information**

#### Product:

Remarks

: No data available



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

### **SECTION 12: Ecological information**

12.1 Toxicity

.1 Toxicity		
Product:		
Ecotoxicology Assessment Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.
Components:		
DISTILLATES (PETROLEUM	), F	IYDROTREATED HEAVY PARAFFINIC:
Toxicity to fish		LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.
LUBRICATING OILS, PETRO	LE	UM, C20-50, HYDROTREATED:
Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Re	evision Date: 19.07.2023	Print Date: 16/10/2023
aquatic invertebrates		Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata ( 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	green algae)): >=
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow	trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information	ition.
Chronic aquatic toxicity	:	Not classified based on available information	ition.
Reaction products of Benze	enea	amine, N-phenyl- with nonene (branched	d):
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg Exposure time: 96 h Test Type: static test Remarks: The toxicological data has bee products of similar composition.	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1 Exposure time: 48 h Test Type: static test Test substance: WAF	00 mg/l
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (a End point: Growth inhibition Exposure time: 72 h Test Type: static test	algae)): 600 mg/l



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Re	evision Date: 19.07.2023	Print Date: 16/10/2023
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information	ation.
Chronic aquatic toxicity	:	Chronic aquatic toxicity Category 4; May harmful effects to aquatic life.	cause long lasting
C14-16-18 Alkyl phenol:			
Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): > 100 mg Exposure time: 96 h Test Type: static test Test substance: WAF	y/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1 Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	00 mg/l
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata ( End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	algae)): > 100 mg/l
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information	ation.
Chronic aquatic toxicity	:	Not classified based on available information	ation.
12.2 Persistence and degradabil	ity		
Components:			
LUBRICATING OILS, PETRO	DLE	UM, C20-50, HYDROTREATED:	
Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B	
Reaction products of Benze	nea	amine, N-phenyl- with nonene (branche	d):
Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B	



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

GIUBUI		
Version: 7.0	Revision Date: 19.07.2023	Print Date: 16/10/2023
C14-16-18 Alkyl phenol:		
Biodegradability	: Result: Readily biodegradable. Remarks: Expert judgement	
12.3 Bioaccumulative potentia	al	
Components:		
Reaction products of Ber	zeneamine, N-phenyl- with nonene (br	anched):
Partition coefficient: n- octanol/water	: log Pow: > 7.5	
C14-16-18 Alkyl phenol:		
Partition coefficient: n- octanol/water	: log Pow: > 7.2	
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB	assessment	
Product:		
Assessment	<ul> <li>This substance/mixture contains r to be either persistent, bioaccumu very persistent and very bioaccum 0.1% or higher.</li> </ul>	llative and toxic (PBT), or
12.6 Other adverse effects		
Product:		
Endocrine disrupting potential	: The substance/mixture does not c considered to have endocrine disr to REACH Article 57(f) or Commis (EU) 2017/2100 or Commission R levels of 0.1% or higher.	upting properties according ssion Delegated regulation
Additional ecological information	: No data available	

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Revision Date: 19.07.2023	Print Date: 16/10/2023
Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways o chemical or used container. Send to a licensed waste management of	
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.	

### **SECTION 14: Transport information**

### 14.1 UN number

	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.3	B Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.4	Packing group		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA_P (Passenger)	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable	
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable	
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable	
Regulation (EC) No 1005/2009 on substances that : Not applicable deplete the ozone layer		
UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)		
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not applicable	
The components of this product are reported in the fo	ollowing inventories:	
TCSI : On the inventory, or in	compliance with the inventory	
TSCA : All substances listed a	as active on the TSCA inventory	
AIIC : On the inventory, or in	compliance with the inventory	
DSL : All components of this	product are on the Canadian DSL	



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0	Revision Date: 19.07.2023	Print Date: 16/10/2023
ENCS	: On the inventory, or in compliance	with the inventory
KECI	: On the inventory, or in compliance	with the inventory
PICCS	: On the inventory, or in compliance	with the inventory
IECSC	: On the inventory, or in compliance	with the inventory
NZIoC	: Not in compliance with the inventor	у

#### 15.2 Chemical safety assessment

#### No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### **SECTION 16: Other information**

#### **Full text of H-Statements**

H304	:	May be fatal if swallowed and enters airways.
H317	:	May cause an allergic skin reaction.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H413	:	May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Chronic :	Long-term (chronic) aquatic hazard
Asp. Tox. :	Aspiration hazard
Skin Sens. :	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;



according to Regulation (EC) No. 1907/2006 NAPA® N237199L VE 0W20 ECO Synthetic Motor Oil

Version: 7.0

Revision Date: 19.07.2023

Print Date: 16/10/2023

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT -Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative** 

#### Further information

Internal information : 000000260374

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN