



TECHNICAL DATA SHEET

GM 5W-30 D1 FS

Product Type 5W-30 SYNTHETIC MOTOR OIL
Product Code N245

Description

A high performance synthetic engine oil suitable for use in a wide range of modern petrol engines.

Benefits

- Low Speed Pre-Ignition reduction
- Enhances fuel economy
- Excellent anti-wear protection
- Exceptional piston cleanliness
- Protection against sludge

Specifications

Always check the owner's manual for the correct oil specification to use.

- API SP, SP-RC, SN PLUS
- ILSAC GF-6A
- FORD WSS-M2C946-A
- GM Dexos1™ Gen 3





TECHNICAL DATA SHEET

GM 5W-30 D1 FS

Product Type 5W-30 SYNTHETIC MOTOR OIL
Product Code N245

Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm ² /s	10,2
Viscosity @ 40°C	ASTM D-445	mm ² /s	58
Viscosity Index	ASTM D-2270	-	165,0
Viscosity @-30°C	ASTM D-5293	mPa.s	4500,0
Total Base Number	ASTM D-2896	mg/KOH/g	7
Pour Point	ASTM D-5949	°C	-42
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	228

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu